View NSN Online: https://aerobasegroup.com/nsn/6830-00-584-3041

COOPER GROUP/TURNER DIV -- LP-175-005G TURNER TORNADO -- 6830-00-584-3041

Product ID:LP-175-005G TURNER TORNADO MSDS Date:05/22/1989 FSC:6830 NIIN:00-584-3041 **MSDS Number: BJCQK** === Responsible Party === Company Name: COOPER GROUP/TURNER DIV Address:821 PARK AVENUE City:SYCAMORE State:IL ZIP:60178 Preparer's Name: J. FRANK FREED CAGE:10725 === Contractor Identific ation === Company Name: COOPER GROUP/TURNER Address:821 PARK AVE City:SYCAMORE State:IL ZIP:60178 Country:US Phone:815-895-4545 CAGE:IO725 Company Name: TURNER CO DIV OF CLEANWELD PRODUCTS CO Address:821 PARK AVE Box:6200 City:SYCAMORE State:IL ZIP:60178-2419 Country:US Phone:815-895-4545 CAGE:61112

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: >90% Other REC Limits:1800 MG/CUM OSHA PEL:1000 PPM ACGIH TLV:AS PHYXIANT; 9192 Ingred Name: PROPYLENE (PROPENE) (SARA III) CAS:115-07-1 RTECS #:UC6740000 Fraction by Wt: 120F. KEEP POTENTIAL IGNITION SOURCES (FIRE, SPARKS) AWAY. AVOID CONTACT W/SKIN. Respiratory Protection:NOT NEEDED UNLESS SPILL EXISTS - CHEMICAL CARTRIDGE OR AIRLINE Ventilation: EXPLOSION PROOF EQUIPMENT OR NATURAL VENTILATION Eve Protection: CHEMICAL GOGGLES Other Protective Equipment:NO SPECIAL GARMENTS REQU IRED. Supplemental Safety and Health HCC:G2 Boiling Pt:B.P. Text:-44F Melt/Freeze Pt:M.P/F.P Text:-305F Decomp Temp:Decomp Text:932-1832F Vapor Pres:208 Vapor Density:1.52 Spec Gravity:0.51 Evaporation Rate & amp; Reference: (ETHYL ETHER = 1): >1 Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR/ODORLESS (ADDITIVE-MERCAPTAN-STRONG-PUNGENT) Percent Volatiles by Volume:100% ========= Stability and Reactivity Data _____

Stability Indicator/Materials to Avoid:YES CHLORINE OR STRONG OXIDIZERS Stability Condition to Avoid:CYLINDER TEMPERATURE >125F, SPARKS, GAS FLAMES & OTHER SOURCES OF IGNITION. Hazardous Decomposition Products:CARBON OXIDES

Waste Disposal Methods:ALLOW SPILLS TO EVAPORATE W/ADEQUATE VENTILATION. BURN UNDER CONTROLLED CONDITIONS USING PRESSURE REGULATOR OR CONTROL VALVE. HAZARD CLASS: FLAMMABLE

GAS; UN1075.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their part

icular situation.