

KERR MANUFACTURING COMPANY -- FORMATRAY LIQUID -- 6520-00-782-0520

=====  
Product Identification  
=====

Product ID:FORMATRAY LIQUID

MSDS Date:04/25/1989

FSC:6520

NIIN:00-782-0520

MSDS Number: BJCQS

=== Responsible Party ===

Company Name:KERR MANUFACTURING COMPANY

Address:28200 WICK ROAD

City:ROMULUS

State:MI

ZIP:48174

Info Phone Num:(313) 946-7800

Emergency Phone Num:(313) 946-7800

CAGE:EO529

=== C

Contractor Identification ===

Company Name:KERR CORP

Address:1717 W COLLINS AVENUE

Box:City:ORANGE

State:CA

ZIP:92867-5422

Country:US

Phone:800-537-7187

CAGE:33339

Company Name:KERR MANUFACTURING COMPANY, DIVISION OF SYBRON COR

Address:28200 WICK ROAD

Box:City:ROMULUS

State:MI

ZIP:48174

Country:US

Phone:(313) 946-7800

CAGE:EO529

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL METHACRYLATE (SARA III)

CAS:80-62-6

RTECS #:OZ5075000

Fraction by Wt: 99%

Other

REC Limits:100 PPM  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM; 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: RASHES.  
INHALATION: HEADACHES, NAUSEA, DROWSINESS, & UNCONSCIOUSNESS.  
INGESTION: GASTRO-INTESTINAL DISTRESS.  
Explanation of Carcinogenicity:NONE  
Effect  
s of Overexposure:EYES: IRRITATION. SKIN: RASHES. INHALATION:  
HEADACHES, NAUSEA, DROWSINESS, & UNCONSCIOUSNESS. INGESTION:  
GASTRO-INTESTINAL DISTRESS.  
Medical Cond Aggravated by Exposure:RASHES

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP &  
WATER. INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN OR GIVE  
ARTIFICIAL RESPIRATION, AS REQUIRED. INGESTION: CALL PHYSICIAN.

=====  
===== F  
Fire Fighting Measures =====

Flash Point:50F  
Lower Limits:1.7%  
Upper Limits:8.2%  
Extinguishing Media:CO2, FOAM, DRY CHEMICALS, WATER FOG  
Fire Fighting Procedures:FIGHT FIRES FROM SAFE DISTANCE. COOL EXPOSED  
MATERIAL W/COLD WATER SPRAY.  
Unusual Fire/Explosion Hazard:SEALED CONTAINERS EXPOSED TO ELEVATED  
TEMPERATURES MAY RUPTURE EXPLOSIVELY DUE TO POLYMERIZATION. VAPORS  
ARE >AIR & MAY TRAVEL.

=====  
===== Accidental Release Measures =====

Spill R

Release Procedures:EVACUATE AREA, ELIMINATE IGNITION SOURCES.  
ABSORB SPILLS W/INERT MATERIAL & TRANSFER TO SUITABLE CONTAINER FOR  
DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DARK PLACE. KEEP AWAY  
FROM IGNITION SOURCES.

Other Precautions:USE ACCORDING TO DIRECTIONS. USE GOOD PERSONAL  
HYGIENE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN VAPORS EXCEED TLV, SELF-CONTAINED BREATHING  
APPARATUS.

Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST VENTILATION TO KEEP