

KERR MANUFACTURING COMPANY -- CRISTOBALITE INLAY INVESTMENT -- 6520-00-958-7092

=====
Product Identification
=====

Product ID:CRISTOBALITE INLAY INVESTMENT

MSDS Date:05/12/1988

FSC:6520

NIIN:00-958-7092

MSDS Number: BJCRG

=== Responsible Party ===

Company Name:KERR MANUFACTURING COMPANY

Address:28200 WICK ROAD

City:ROMULUS

State:MI

ZIP:48174

Info Phone Num:(313) 946-7800

Emergency Phone Num:(313)

946-7800

CAGE:EO529

=== Contractor Identification ===

Company Name:KERR CORP

Address:1717 W COLLINS AVENUE

Box:City:ORANGE

State:CA

ZIP:92867-5422

Country:US

Phone:800-537-7187

CAGE:33339

Company Name:KERR MANUFACTURING COMPANY, DIVISION OF SYBRON COR

Address:28200 WICK ROAD

Box:City:ROMULUS

State:MI

ZIP:48174

Country:US

Phone:(313) 946-7800

CAGE:EO529

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE

CAS:14464-46-1

RTECS #:VV7

325000
Fraction by Wt: 73.0%
Other REC Limits:0.05 MG/CUM NIOSH
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:YES
Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: DRY.
INHALATION: LUNG INJURY (SILICOSIS), PULMONARY FIBROSIS & DEATH.
INGESTION: HARDENS WHEN WETTED & MAY RESULT IN AN OBSTRUCTION.

Ex
planation of Carcinogenicity:IARC REPORTS LIMITED EVIDENCE OF THE
CARCINOGENICITY OF CRYSTALLINE SILICA TO HUMANS. IARC CLASS 2A.
Effects of Overexposure:EYE: IRRITATION. SKIN: DRY. INHALATION: LUNG
INJURY (SILICOSIS), PULMONARY FIBROSIS & DEATH. INGESTION: HARDENS
WHEN WETTED & MAY RESULT IN AN OBSTRUCTION.

=====
===== First Aid Measures =====

First Aid:EYE: WASH W/LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS,
GET MED ATT. SKIN: WASH W/SOAP &
WATER. INHALATION: MOVE EXPOSED
PERSON TO FRESH AIR. INGESTION: CONSULT PHYSICIAN.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA OF SPILL OR RELEASE. SWEEP UP.
AVOID UNNECESSARY STIRRING OR HANDLING IN ORDER TO PREVENT
FORMATION OF DUST.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DON'T BREATHE DUST. KEEP CONTAINER
CLOSED. USE ACCORDING TO DIRECTIONS.
Other P
recautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH-APPROVED EQUIPMENT.
Ventilation:USE SUFFICIENT LOCAL EXHAUST TO REDUCE THE LEVEL OF
RESPIRABLE CRYSTALLINE SILICA TO THE PEL.
Protective Gloves:OPTIONAL
Eye Protection:GOGGLES
Work Hygienic Practices:USE GOOD PERSONAL HYGIENE.
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:2230C
Melt/Freeze Pt:M.P/F.

P Text:1600F
Vapor Pres:0
Spec Gravity:2.6
Solubility in Water:INSOLUBLE
Appearance and Odor:OFF WHITE, ODORLESS SOLID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, HYDROFLUORIC ACID WHICH PRODUCES THE CORROSIVE GAS
SILICON TETRAFLUORIDE
Stability Condition to Avoid:NONE

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.