

FIBER MATERIALS, INC. -- FLEXFRAM 605 PT A -- 8030-00-097-9088

=====  
Product Identification  
=====

Product ID:FLEXFRAM 605 PT A

MSDS Date:11/18/1992

FSC:8030

NIIN:00-097-9088

Kit Part:Y

MSDS Number: BJDMS

=== Responsible Party ===

Company Name:FIBER MATERIALS, INC.

Address:5 MORIN ST

City:BIDDEFORD

State:ME

ZIP:04005

Country:US

Info Phone Num:207-282-5911

Emergency Phone Num:207-282-5911;207-828-6  
209

CAGE:KO060

=== Contractor Identification ===

Company Name:FIBER MATERIALS INC

Address:BIDDEFORD INDUSTRIAL PARK

Box:City:BIDDEFORD

State:ME

ZIP:04005

Country:US

Phone:207-282-5911

CAGE:62500

Company Name:FIBER MATERIALS, INC.

Address:5 MORIN ST

Box:City:BIDDEFORD

State:ME

ZIP:04005

Country:US

Phone:207-282-5911

CAGE:KO060

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TRIETHYLENETETRAMINE; (TETA (TRIETHYLENETETRAMINE 70%)).

LD50 (ORAL RAT):4350 MG/KG.

CAS:112-24-3  
RTECS #:YE6650000  
Fraction by Wt: 7.0%  
OSHA PEL:N/K  
ACGIH TLV:N/K

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:INGREDIENT 1  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:MAY CAUSE SKIN BURNS, ALLERGIC SKIN  
REACTIONS. INGESTION MAY CAUSE BURNS OF MOUTH AND THROAT. MAY CAUSE  
RESPIRATORY SENSITIZATION IN SUSCEPTIBLE INDIVIDUALS OR THROAT

IRRITATION.

Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:PRIMARY IRRITATION OF SKIN ON PROLONGED  
CONTACT. IRRITATING TO THE EYES. MAY CAUSE SEVERE IRRITATION WITH  
CORNEAL INJURY, EVEN BLINDNESS.  
Medical Cond Aggravated by Exposure:ALLERGIES AND/OR OTHER RESPIRATORY  
CONDITIONS.

=====  
===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR, GET MD. EYE: FLUSH THOROUGHLY  
W/WATER 30 MIN. GET MD IMMEDIATELY. SKI  
N: WASH W/SOAP AND WATER.  
INGEST: INDUCE VOMITING AND GET MD IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:315F,157C  
Extinguishing Media:CO\*2, DRY CHEMICAL  
Fire Fighting Procedures:FOR LARGE FIRES, USE WATER SPRAY, FOG, OR  
FOAM. DIKE WATER RUN-OFF. PREVENT ENTRY INTO SEWERS OR NATURAL  
WATERS. WEAR FULL PROTECTIVE EQUIPMENT.  
Unusual Fire/Explosion Hazard:TOXIC FUMES WILL BE EVOLVED IF UNMIXED  
MATERIAL IS INVO

LVED IN A FIRE. WEAR SCBA.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE. NIOSH APPROVED RESP PROT AND OTHER PROT EQUIP AS NECESSARY TO PREVENT SKIN & EYE CONTACT. PUMP OR SHOVEL INTO SALVAGE DRUM. SOAK UP RESIDUE & SML SPILLS W/ABSORBENT MAT SUCH AS CLAY & PUT IN TIG HT CONTAINER. IF USE SOLVNT, WATCH FIREHAZARDS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN TIGHT, STURDY CONTAINERS. HANDLE I/A/W HAZARD POTENTIAL.

Other Precautions:REMOVE CONTAMINATED CLOTHING & PROTECTIVE GEAR. DECONTAMINATE. DESTROY LEATHER ARTICLES, INCLUDING SHOES THAT CANNOT BE DECON. ANSI CLASSIFICATION 2. REMOVAL OF CURED MATERIAL SHOULD BE ACCOMPLISHED W /NIOSH APPROVED RESPIRATORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESP W/ORGANIC VAPOR CARTRIDGE AS REQUIRED TO PREVENT VAPOR OVEREXPOSURE.

Ventilation:LOCAL: IN CONFINED MIXING & APPL. AREAS. MECH: REQUIRED TO PREVENT OVEREXPOSURE.

Protective Gloves:RUBBER GLOVES TO PREVENT SKIN CONTACT.

Eye Protection:GOGGLES OR FACE SHIELD.

Other Protective Equipment:AS NECESSARY TO PREVENT BODY CONTACT. EYE WASH & DELUGE SHOWER .

Work Hygienic Practices:AVOID SMOKING, EATING, AND DRINKING IN THE WORK AREA.

Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:600F,316C

Vapor Pres:.01

Vapor Density:9

Spec Gravity:1.201 (H\*20=1)

Solubility in Water:SLIGHT

Appearance and Odor:BLACK VISCOUS LIQUID, MERCAPTAN ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, CHLORINATED ORGANIC COMPOUNDS.

Stability Condition to Avoid:REACTS WITH CONSIDERABLE HEAT WITH HOT RESINS.

H

azardous Decomposition Products:CO\*2, ALDEHYDES, ACIDS, NO\*2, SO\*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I/A/W FED, STATE AND LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all li

ability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.