

MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY -- RARUS 427 -- 9150-01-315-9319

===== Product Identification =====

Product ID:RARUS 427

MSDS Date:12/30/1992

FSC:9150

NIIN:01-315-9319

MSDS Number: BJDQC

=== Responsible Party ===

Company Name:MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY

Address:PENNINGTON-ROCKY HILL RD

City:PENNINGTON

State:NJ

ZIP:08534

Country:US

Info Phone Num:609-662-452

5

Emergency Phone Num:609-737-4411/800-424-9300(CHEMTREC)

CAGE:0AHK0

=== Contractor Identification ===

Company Name:MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY

Address:PENNINGTON-ROCKY HILL RD

Box:City:PENNINGTON

State:NJ

ZIP:08534

Country:US

CAGE:0AHK0

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

B

ox:City:HARVEY  
State:LA  
ZIP:70058  
Country:US  
Phone:504-366-4542  
CAGE:0T5C6

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC  
CAS:64742-54-7  
RTECS #:PY8035500  
Fraction by Wt: >95%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PROPIETARY COMPONENT  
Fraction by Wt: 450F,>232C  
Lower Limits:0.6%  
Upper Limits:7.0%  
Extinguishing Media:WATER FOG,CO2,FOAM/DRY CHEMICAL.WATER  
/FOAM MAY  
CAUSE FROTHING.IF A LEAK NOT IGNITED,USE WATER SPRAY TO DISPERSE  
VAPORS.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS IN + PRESSURE MODE.  
COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.  
Unusual Fire/Explosion Hazard:FUMES, SMOKE, CARBON MONOXIDE, CARBON  
DIOXIDE AND OTHER DECOMPOSITION PRODUCTS MAY FORM.

=====  
Accidental Release Measures  
=====

Spill Release Procedures  
:WEAR PROTECTIVE EQUIPMENTS. VENTILATE AREA.  
STOP LEAK. RECOVER FREE PRODUCT. CONTAIN LARGE SPILL. PUMP IT TO  
TRUCK. SOAK UP RESIDUE/SMALL SPILLS WITH CLAY/SAND. TRANSFER TO  
CONTAINER FOR DISPOSAL. REP ORT SPILLS AS REQUIRED. KEEP PRODUCT  
OUT OF SEWERS

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORAGE- STORE IN COOL PLACE. KEEP  
AWAY FROM HEAT, FLAME & STRONG OXIDANTS.  
Other Precautions:EMPTY CONTAINERS MAY CONTAIN P

PRODUCT RESIDUE WHICH

COULD INCLUDE FLAMMABLE OR EXPLOSIVE VAPORS. CONSULT APPROPRIATE FEDERAL, STATE & LOCAL AUTHORITIES BEFORE REUSING, RECONDITIONING, RECLAIMING, RECYCLING/DISPOSING OF EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS AND MISTS. WEAR SUPPLIED-AIR RESPIRATOR

PROTECTION IN CONFINED OR ENCLOSED SPACES, IF NEEDED.

Ventilation: USE LOCAL EXHAUST TO CAPTURE VAPOR, MISTS OR FUMES, IF NECESSARY. PROVIDE SUFFICIENT VENTILATION TO PREVENT EXPLOSION.

Protective Gloves: CHEMICAL-RESISTANT, IF NEEDED (NITRILE)

Eye Protection: CHEMICAL SPLASH GOGGLES/FACE SHIELD

Other Protective Equipment: EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

MINIMIZE BREATHING VAPOR, MIST OR FUMES. AVOID PROLONGED OR REPEATED SKIN CONTACT. LAUNDER OR DRY-CLEAN CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING

===== Physical/Chemical Properties =====

HCC: V6

Boiling Pt: B.P. Text: >600F, >316C

Vapor Pres: