

KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS -- NITROGEN A800500-10 -- 4920-00-870-0582  
===== Product Identification =====

Product ID:NITROGEN A800500-10  
MSDS Date:05/20/1986  
FSC:4920  
NIIN:00-870-0582  
MSDS Number: BJDTH  
=== Responsible Party ===  
Company Name:KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS  
Address:2500 AIRPORT DRIVE  
City:WILSON  
State:NC  
ZIP:27893-9604  
Country:US  
Info Phone Num:307-744-5487

Emergency Phone Num:919-237-7004  
CAGE:61423  
=== Contractor Identification ===  
Company Name:KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS  
Address:2500 AIRPORT DRIVE  
Box:City:WILSON  
State:NC  
ZIP:27893-9604  
Country:US  
Phone:252-237-7004  
CAGE:61423

===== Composition/Information on Ingredients =====

Ingred Name:NITROGEN  
CAS:7727-37-9  
RTECS #:QW9700000  
Fraction by Wt: 100%  
ACGIH TLV:ASPHYXIAN; 9192

===== Hazards Identification =====

LD50 LC50 Mixtu

re:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:CHRONIC:N/A.

INHALE:HEADACHE,DROWSINESS,DIZZINESS,EXCITATION, EXCESS SALIVATION,  
VOMITING AND UNCONSCIOUSNESS. LIQUID CONTACT MAY CAUSE FROSTBITE.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS

Medical Cond Aggravated by Exposure:THE TOXICOLOGY, PHYSICAL AND  
CHEMICAL PROP

ERTIES OF THE MATERIAL DO NOT SUGGEST THAT  
OVEREXPOSURE IS LIKELY TO AGGRAVATE EXISTING MEDICAL CONDITIONS.

=====  
===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR,GET MD. GIVE ART. RESP. IF NECESSARY OR  
OXYGEN. FLUSH EYES W/WATER AT LEAST 15 MIN. FOR EXPOSURE TO LIQUID,  
WARM FROSTBITE AREA WITH WATER (NOT TO EXCEED 105F). IN CASE OF  
MASSIVE EXPOSURE, REMOVE CLOTHES AND SHOWER W/WARM WATER. NOTE:  
THERE IS NO SPECIFIC ANTIDOTE. DIR  
.TREATMENT AT CNTRL OF SYMPTOM.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:NITROGEN CANNOT CATCH FIRE

Fire Fighting Procedures:USE MEDIA APPROPRIATE FOR SURROUNDING  
FIRE.EVACUATE PERSONNEL FROM DANGER AREA.DELUGE CONTAINER W/WATER  
SPRAY FROM MAX.DISTANCE TIL COOL.MOVE CONTAINERS AWAY.

Unusual Fire/Explosion Hazard:GAS CANNOT CATCH FIRE.CONT.MAY RUPTURE  
DUE TO HEAT OR FIRE.NO PART OF A CONT.SHOULD BE >52C.MOST  
CONTAINERS WILL VENT CO  
NTENTS WHEN EXPOSED TO HIGH TEMPS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL. USE SCBA WHERE NEEDED.  
VENTILATE AREA WHERE LEAK OCCURED. TEST AREA FOR SUFFICIENT OXYGEN  
PRIOR TO PERMITTING RE-ENTRY OF PERSONNEL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE & USE W/ADEQUATE VENTILATIONS.  
MIXING TWO OR

MORE GASES OR LIQUIDIFIED GASES MAY COMBINE TO CREATE UNEXPECTED HAZARD.OBTAIN SAFETY INFORMATION.

Other Precautions:NEVER WORK ON A PRESSURIZED SYSTEM. IF THERE IS A LEAK,CLOSE THE CYLINDER VALVE,BLOW DOWN THE SYSTEM BY VENTING TO A SAFE PLACE, THEN REPAIR THE LEAK.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PER OSHA 29 CFR 1910.134 - ACCEPTABLE TO MSHA AND NIOSH

Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL ACCEPTABLE

Protecti

ve Gloves:USE FOR HANDLING CYLINDERS & 1910.132.

Eye Protection:I/A/W OSHA CFR 1910.133

Other Protective Equipment:METATORSAL SHOES FOR CYLINDER HANDLING, IAW OSHA 29 CFR 1910.132

Work Hygienic Practices:GOOD HYGIENE PRACTICE AS WITH ANY INDUSTRIAL CHEMICAL

Supplemental Safety and Health

THIS IS PART "B" OF A TWO PART PRODUCT, WHICH IS NOT A KIT.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:-320F,-195C

Melt/Freeze Pt:M.P/F.P Text:-346F,-210C

Vapor Pres:@ 20C GAS

Vapor Density:0.967

Spec Gravity:1.2506G/L @ 0C

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS,ODORLESS GAS AT AMBIENT TEMP AND PRESSURE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

UNDER CERTAIN CONDITIONS NITROGEN CAN REACT VIOLENTLY W/LITHIUM,NEODYMIUM,TITANIUM OR OZONE.

Stability Condition to Avoid:CAUTION HIGH PRESSURE GAS

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods: SLOWLY RELEASE INTO ATMOSPHERE. DISCARD ANY PRODUCT, RESIDUE DISPOSABLE CONTAINERS OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER I/A/W FED, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.