

FISKE BROS REFINING CO -- LUBRIPLATE 100 SERIES -- 9150-01-025-6028

=====
Product Identification
=====

Product ID:LUBRIPLATE 100 SERIES

MSDS Date:06/01/1989

FSC:9150

NIIN:01-025-6028

MSDS Number: BJDTR

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:1

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-91

50

Preparer's Name:ROBERT J. SIBILIA

CAGE:73219

=== Contractor Identification ===

Company Name:AQUA-CHEM INC.; CLEAVER-BROOKS DIV.

Address:1500 LEHMAN STREET

Box:City:LEBANON

State:PA

ZIP:17024-3337

Country:US

Phone:717-274-7853

CAGE:12793

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:NYE LUBRICANTS INC

Address:12 HOWLAND RD

Box:City:FAIR HAVEN

State:MA

ZIP:02719

Country:US

Phone:508-996-6

721
CAGE:98354
Company Name:STRATEGIC PROCUREMENT SERVICE INC, W AND W LOGISTICS DIV
Address:2 MADISON ROAD
Box:City:FAIRFIELD
State:NJ
ZIP:07004
Country:US
Phone:973-575-6620
CAGE:79343

=====
Composition/Information on Ingredients
=====

Ingred Name:OIL MIST IN AIR
RTECS #:RI7400000
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:N
O Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION.PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. LO W ORDER OF ACUTE ORAL TOXICITY. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond A
ggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:FLUSH W/WATER 15 MIN OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, GET MD. SKIN: REMOVE CONTAM CLOTHING, WASH W/ SOAP & WATER. IF ANY INJECTED UNDER SKIN, GET MD IMMED. INHAL: AT ROOM TEMP, NO T A PROBLEM. IF NECESSARY, REMOVE FROM EXPOSURE & GET MD. INGEST: GET MD IMMEDIATELY.

=====
Fire Fighting Measures
=====

=====

Flash Point Method:COC

Flash Point:360F,182C

Lower Limits:1%

Upper Limits:7%

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY

Fire Fighting Procedures:COOL EXPOSED CONTAINERS W/ WATER. USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX W/ STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

=====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER W/SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS AND WATER COURSES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:

AVOID BREATHING OIL MIST. REMOVE OIL-SOAKED CLOTHING AND LAUNDRY BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED

Protective Gloves:OIL RESISTANT, IF NEEDED

Eye Protection:GOGGLES

Other Protective Equipment:OIL RESISTANT APRON, IF NEEDED.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER

=====

Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:550F,288C

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.89-0.93

Evaporation Rate & Reference: