View NSN Online: https://aerobasegroup.com/nsn/8040-01-224-4909

## BONDED PRODUCTS INC -- MULTIPURPOSE EPOXY-POLYAMIDE 5808332 -- 8010-01-224-4909

Product ID:MULTIPURPOSE EPOXY-POLYAMIDE 5808332

MSDS Date:05/08/1990

FSC:8010

NIIN:01-224-4909

Kit Part:Y

MSDS Number: BJDVS === Responsible Party ===

Company Name: BONDED PRODUCTS INC

Address:439 S BOLMAR ST

Box:39

City:WEST CHESTER

State:PA

ZIP:19381-0039 Country:US

Info Phone Num:2

15-696-9220

Emergency Phone Num:215-696-9220 Preparer's Name:A. NICHOLAS ROSA

CAGE:19092

=== Contractor Identification ===

Company Name: ABBEY COLOR INC DBA ABBEY PRODUCTS AND BONDED

Address:400 E TIOGA ST Box:City:PHILADELPHIA

State:PA

ZIP:19134-1127

Country:US

Phone:215-739-9960

CAGE:19092

Company Name: CALIFORNIA GASKET CORP

CAGE:86044

Company Name: ITW PHILADELPHIA RESINS

Address:130 COMMERCE DR Box:City:MONTGOMERYVILLE

State:PA ZIP:18936 Country:US

Phone:215-855-8450

CAGE:20420

\_\_\_\_\_


Composition/Information on Ingredients ======== Ingred Name: EPOXIDE CAS:25068-38-6 RTECS #:KC2100000 Fraction by Wt: 78% Ingred Name: QUSO WR55-TLV 6 MG/M3 TOTAL DUST, 3 MG/M3 RESPIRABLE DUST CAS:112945-52-5 RTECS #: VV7310000 Fraction by Wt: 22% OSHA PEL:80 MG/M3% **ACGIH TLV:SEE INGREDIENTS** LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity: NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: NONE SPECIFIED BY MANUFACTURER. **Explanation of Carcinogenicity: NOT RELEVANT** Effects of Overexposure: WORKING IN CONFINED AREA W/ POOR VENTILATION CAN CAUSE NAUSEA. PROLONGED CONTACT OR EXPOSURE CAN CAUSE IRRITATION OF SKIN & EYES. CAN CAUSE IRRITATION AND REDNESS OF SKIN. ABDOMINAL DISCOMFORT IF INGE STED Medical Cond Aggravated by Exposure: ALLERGY, ECZEMA, OR EXISTING SKIN CONDITIONS. NEEDED, GET MD. SKIN: WASH THOROUGHLY W/ SOAP AND WATER, GET MD IF

======= First Aid M

First Aid:INHAL: REMOVE TO FRESH AIR, GIVE OXYGEN OR ART RESP IF IRRITATION PERSISTS. EYES: FLUSH W/ WATER 15 MIN. GET MD. INGEST: GIVE LARGE Q UANTITIES OF WATER, GET MD.

============ Fire Fighting Measures =========================

Flash Point Method:COC Flash Point:>400F,>204C Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting Procedures:WEAR FULL PROTECTI



Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS AND MINERAL ACIDS
Stability Condition to Avoid:ELEVATED TEMPERATURES
Hazardous Decomposition Products: OXIDES OF CARBON AND ALDEHYDES

======= Disposal Considerations ===========

Waste Disposal Methods:RECLAIM, IF POSSIBLE. REACT THIS PART A W/ PART B. DISPOSE I/A/W FED, STATE AND LOCAL REGS

Disclaimer (provided with this information by the compiling ag encies):

=== Stability and Reactivity Data =========

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.