

SOUTH COAST TERMINALS INC -- SCT SF/CD MOTOR OIL SAE 30 (WS234) -- 9150-00-189-6729

=====
Product Identification
=====

Product ID:SCT SF/CD MOTOR OIL SAE 30 (WS234)

MSDS Date:03/05/1990

FSC:9150

NIIN:00-189-6729

MSDS Number: BJFNF

=== Responsible Party ===

Company Name:SOUTH COAST TERMINALS INC

Address:7401 WALLISVILLE RD

Box:15535

City:HOUSTON

State:TX

ZIP:77020-3555

Country:US

Info Phone Num:71

3-672-2401 EXT 232

Emergency Phone Num:713-672-2401-232/800-424-9300(CHEM)

CAGE:1L506

=== Contractor Identification ===

Company Name:SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

Box:15535

City:HOUSTON

State:TX

ZIP:77020

Country:US

Phone:713-672-2401/800-424-9300(CHEMTREC)

CAGE:1L506

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL/BASE OIL/LUBRICATING OIL BASESTOCK

CAS:8002-05-9

RTECS #:SE7175000

Fraction by Wt: 80-90%

Other REC Limits:

NONE SPECIFIED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PHOSPHORODITHIOIC ACID, ZINC SALT
RTECS #:TD5110000
Other REC Limits:NONE SPECIFIED

Ingred Name:THE MANUFACTURER STATES THAT THE IDENTITIES OF INGREDIENTS
THAT ARE TRADE SECRETS ARE EXCLUDED FROM THE MSDS LIST.
RTECS #:9999999ZZ
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Health Hazards Acute and

Chronic:ACUTE-EYE:IRRITATION.SKIN:IRRITATION.INHALE:EXPOSURE TO
HEATED MIST/VAPOR MAY CAUSE
IRRITATION.INGESTION:IRRITATION.CHRONIC-SKIN:DERMATITIS.
Effects of Overexposure:EYE:DIRECT CONTACT MAY CAUSE BURNING, TEARING,
AND REDNESS.SKIN:REDNESS AND BURNING.INHALATION:IRRITATION TO NOSE
AND THROAT.INGESTION:IRRITATION TO THE DIGESTIVE TRACT.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR

RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH CLEAN WATER.IF IRRITATION/REDNESS PERSISTS,SEE
A DOCTOR.SKIN:WASH WITH SOAP & WATER.IF IRRITATION PERSISTS, SEE A
PHYSICIAN.INHALATION:MOVE TO FRESH AIR.IF IRRITATION PERSISTS, SEE
A DO CTOR.INGESTION:DON'T INDUCE VOMITING.CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:200C(MI
N)
Extinguishing Media:WATER FOG, CARBON DIOXIDE, FOAM, DRY CHEMICAL, SAND
OR EARTH. WATER AND FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:RESPIRATORY PROTECTION AND EYE PROTECTION
REQUIRED FOR FIRE FIGHTING PERSONNEL.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:TREAT AS AN OIL SPILL. CONTAIN AND REMOVE BY
MECHANICAL MEANS.
Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling an

d Storage =====

Handling and Storage Precautions:NONE NORMALLY REQUIRED.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.

Protective Gloves:NEOPRENE, NITRILE, PVC OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:NONE

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYG

IENE PRACTICES AND

RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

THE MOTOR OIL WS234 IS PART A, AND THE MULTILUBE FN204 IS PART B.

MEDICAL OPINION IS DIVIDED FOR LARGE INGESTION.

EMESIS OR LAVAGE HAS BEEN RECOMMENDED FOR THOSE PETROLEUM PROD UCTS WHICH HAVE A HIGH ORAL TOXICITY.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>500F,>260C

Vapor Pres:1

Spec Gravi

ty:.87-.88

pH:7

Evaporation Rate & Reference: