View NSN Online: https://aerobasegroup.com/nsn/4210-00-165-4703

BUCKEYE FIRE EQUIPMENT COMPANY -- ABC DRY CHEMICAL -- 4210-00-165-4703

Product ID:ABC DRY CHEMICAL

MSDS Date:03/20/1989

FSC:4210

NIIN:00-165-4703

MSDS Number: BJHTJ === Responsible Party ===

Company Name: BUCKEYE FIRE EQUIPMENT COMPANY

Address:102 INDUSTRIAL DIRVE

City:KINGS MOUNTAIN

State:NC ZIP:28086 Country:US

Info Phone Num:704-739-7415 Emergency Phone Num:70

4-739-7415 CAGE:57658

=== Contractor Identification ===

Company Name: BUCKEYE FIRE EQUIPMENT CO

Address:110 KINGS RD

Box:428

City:KINGS MOUNTAIN

State:NC ZIP:28086 Country:US

Phone:704-739-7415

CAGE:57658

======= Composition/Information on Ingredients ========

Ingred Name:MICA - SILICATES (< 1% CRYSTALLINE SILICA)

CAS:12001-26-2 RTECS #:VV8760000 OSHA PEL:20 MPPCF

ACGIH TLV:3 MG/M3 RDUST; 9293

Ingred Name:BARIUM SULFATE

CAS:7727-43-7

RTECS #:CR0600000

OSHA PEL:15 MG/M3 TDUST

ACGIH

=========== Hazards Identification ==============
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN: DERMATITIS/IRRITATES. INHALATION: LUNG INURY OR DISEASE, PNEUMACONOSIS/POSITIVE CHEST X-RAYS, IRRITATES RESPIRATORY PASSAGES. TREAT AS A MINERAL DUST. INGESTION: SORE THROAT, ABDOMINAL PAIN, NAU SEA, VOMITING/HARMFUL EYES: IRRITATES.
Exp Ianation of Carcinogenicity:NONE Effects of Overexposure:SKIN: DERMATITIS, IRRITATES. EYES: IRRITATES. INHALATION: LUNG INJURY OR DISEASE, PNEUMACONOSIS/POSITIVE CHEST X-RAYS, IRRITATES RESPIRATORY PASSAGES. INGESTION: SORE THROAT, ABDOMINAL PAIN, NAUSEA, V OMITING/HARMFUL.
======================================
First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: TRANSPORT TO FRESH AIR. INGESTION: RINSE/DRINK WATER.
CONSULT PHYSICIAN.
======================================
Flash Point:NONE Extinguishing Media:THIS MATERIAL IS AN EXTINGUISHING AGENT. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE
======== Accidental Release Measures ==========
Spill Release Procedures:CONTAIN SPILLS/SWEEP UP.
======================================
Handling and Storage Precautions:STORE IN CLOSED MOISTURE-FREE CONTAINE

TLV:10 MG/M3 TDUST; 9293

RS IN A COOL DRY LOCATION. AVOID UNNECESSARY DUST. DON'T MIX THIS PRODUCT W/OTHER EXTINGUISHING AGENTS. Other Precautions: THIS PRODUCT IS WATER REPELLANT COATED. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: DUST RESPIRATOR REQUIRED WHEN TLV IS EXCEEDED. Ventilation:LOCAL EXHAUST/MECHANICAL: RECOMMENDED Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES Other Protective Equipment: NONE REQUIRED Work Hygienic Practices: USE GOOD HYGIENE/GOO D HOUSEKEEPING PRACTICES. Supplemental Safety and Health ======== Physical/Chemical Properties =========== HCC:G3 Spec Gravity:0.82 Solubility in Water: NONE Appearance and Odor:YELLOW POWDER W/NO CHARACTERISTIC ODOR. ======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG BASES, BARIUM SULPHATE SILICA Stability Condition to Avoid:STORAGE >350F. Hazardous Decomposition Products: AMMONIA, CO, NITROGEN OXIDES

====== Disposal Considerations ===========

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing t

his

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.