

KALCOR COATING COMPANY -- CLEAR SANDING SEALER TTS-190-F -- 8010-00-663-2673

=====
Product Identification
=====

Product ID: CLEAR SANDING SEALER TTS-190-F

MSDS Date: 12/06/1988

FSC: 8010

NIIN: 00-663-2673

MSDS Number: BJKPH

=== Responsible Party ===

Company Name: KALCOR COATING COMPANY

Address: 37721 STEVENS BLVD

City: WILLOUGHBY

State: OH

ZIP: 44094

Country: US

Info Phone Num: 216-946-4700

Emergency Phone

Num: 216-381-5614

Preparer's Name: VS

CAGE: 33201

=== Contractor Identification ===

Company Name: KALCOR COATING CO

Address: 37721 STEVENS BLVD

Box: City: WILLOUGHBY

State: OH

ZIP: 44094-6231

Country: US

Phone: 216-946-4700

CAGE: 33201

=====
Composition/Information on Ingredients
=====

Ingred Name: TOLUENE (SARA III)

CAS: 108-88-3

RTECS #: XS5250000

Fraction by Wt: 5.32%

Other REC Limits: 150 PPM STEL

OSHA PEL: 200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 6.09%

Other REC Limits:150 PPM STEL

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 11.81%

Other REC Limits:500 PPM STEL

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS

:117-81-7

RTECS #:TI0350000

Fraction by Wt: 1.05%

OSHA PEL:5 MG/M3/10 STEL

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: THAN AIR

Spec Gravity:0.9 (H2O=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:VISCOUS LIQUID - HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Mate

rials to Avoid: YES
STRONG OXIDIZERS.

Hazardous Decomposition Products: WHEN HEATED TO DECOMPOSITION, AS IN WELDING, TOXIC FUMES MAY BE PRODUCED.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. BEFORE ATTEMPTING CLEAN-UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTIONS OF THIS SHEET.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.