

MALTER INTERNATIONAL BULK CHEMICALS DIVISION -- VV-P-236 -- 9150-00-250-0933

===== Product Identification =====

Product ID:VV-P-236

MSDS Date:06/01/1988

FSC:9150

NIIN:00-250-0933

MSDS Number: BJKWY

=== Responsible Party ===

Company Name:MALTER INTERNATIONAL BULK CHEMICALS DIVISION

Address:80 FIRST STREET

City:GRETNA

State:LA

ZIP:70053

Country:US

Info Phone Num:504-362-3232

Emergency Phone Num:504

-362-3232

CAGE:27978

=== Contractor Identification ===

Company Name:MALTER INTERNATIONAL BULK CHEMICAL DIVISION

Address:80 FIRST STREET

Box:City:GRETNA

State:LA

ZIP:70053

Country:US

Phone:504-362-3232, OR 800-535-4095

CAGE:27978

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

===== Hazar

ds Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE
Explanation of Carcinogenicity:THE COMPONENTS OF THIS PRODUCT HAVE NOT
SHOWN ANY EVIDENCE OF BEING CARCINOGENIC.
Effects of Overexposure:NONE

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH COOL WATER FOR 15 MIN.CALL A
PHYSICIAN.SKIN:FOR MOLTEN PETROLEUM,
FLUSH IMMEDIATELY WITH COLD
WATER.CALL A DOCTOR.FOR SOLIDIFIED PETROLATUM,REMOVE EXCESS WITH
PAPER TOWEL,WASH WITH SOAP & WATER.INHALED:NO DATA AVAILABLE.CALL
A PHYSICIAN.INGESTED:CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>400F,>204C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, DRY CHEMICAL
OR SAND/EARTH.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PR
TECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE.WATER SPRAY
IS AN UNSUITABLE EXTINGUISHING AGENT.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF LEAK AND DIKE UP LARGE SPILLS. AFTER
COOLING AND SOLIDIFICATION, SCRAP AND/OR SHOVEL UP MATERIAL.
FINALLY,CLEAN AREA WITH AN OIL ABSORBENT MATERIAL.
Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

H

Handling and Storage Precautions:STORE AWAY FROM FLAME, HEAT (200F MAX)
AND STRONG OXIDIZING AGENTS. AVOID SKIN AND EYE CONTACT.

Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NO DATA AVAILABLE.

Ventilation:NONE NORMALLY REQUIRED.

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:WEAR A FACE SHIELD OVER SAFETY GLASSES.

Other Protective Equipment:WEAR OVERALLS. EYE WASH STATION & SAFETY
SHOWER.

Work

Hygienic Practices:READ ALL LABELS CAREFULLY BEFORE USING. USE
GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V6

Melt/Freeze Pt:M.P/F.P Text:110F,43C

Solubility in Water:NIL

Appearance and Odor:SEMI-SOLID, OIL LIKE, OPAQUE, YELLOW OR BROWN COLOR

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Con

dition to Avoid:NONE

Hazardous Decomposition Products:NONE

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaim

s all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.