

CON-LUX COATINGS, INC. -- TT-P-620C, COMP 1 WHITE 37875 -- 8010-00-059-8822  
===== Product Identification =====

Product ID:TT-P-620C, COMP 1 WHITE 37875  
MSDS Date:08/01/1990  
FSC:8010  
NIIN:00-059-8822  
MSDS Number: BJLCM  
=== Responsible Party ===  
Company Name:CON-LUX COATINGS, INC.  
Address:226 TALMADGE ROAD  
City:EDISON  
State:NJ  
ZIP:08818-0847  
Country:US  
Info Phone Num:201-287-4000, 8:30 - 5:00 MON-F  
RI  
Emergency Phone Num:800-424-9300 CHEMTREC  
Preparer's Name:ED DOENGES  
CAGE:60189  
=== Contractor Identification ===  
Company Name:CON-LUX COATINGS INC  
Address:226 TALMADGE RD  
Box:847  
City:EDISON  
State:NJ  
ZIP:08818-0847  
Country:US  
Phone:732-287-4000  
CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 19.2%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM; 9293

Ingred Name:

TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 6.4%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 19.2%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:MAGNESIUM SILICATE (TALC)

CAS:14807-96-6

RTECS #:VV7720000

Fraction by Wt: 25.6%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3

ACGIH

TLV:2 MG/M3

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT. CHRONIC: REPORTS HAVE ASSOCIATED PROLONGED OCCUPATIONAL OVEREXPOSURE TO SO LVENTS WITH PERMANENT BRAIN AND NERVOUSSYSTEM DAMAGE.

Effe

cts of Overexposure:HEADACHE, NAUSEA AND DIZZINESS.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR. RESTORE RESPIRATION IF NECESSARY. TREAT SYMPTOMATICALLY. EYE CONTACT: FLUSH IMMEDIATELY WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES. CONSULT A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. AND INGESTION: DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN IMMEDIA

TELY.

===== Fire Fighting Measures =====

Flash Point:105 F/40.5 C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:CO2, DRY CHEMICAL.

Fire Fighting Procedures:USE OF A SCBA IS RECOMMENDED FOR FIRE FIGHTERS, WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS & COOLING CONTAINERS EXPOSED TO HEAT AND FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WEAR APPROPRIATE P

PERSONAL PROTECTION EQUIPMENT AND APPROVED RESPIRATOR. CONTAIN SPILL AND PUT IN VAPOR TIGHT CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN AREAS TO COMPLY WITH ANSI/NFPA 30 FLAMMABLE AND COMBUSTIBLE LIQUID CODE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROVED NIOSH/MSHA ORGANIC VAPOR RESPIRATOR

Ventilation:SUFFICIENT VENTILATION, IN VOLUME & PATTERN REQUIRE D TO

KEEP HAZARDOUS MATERIAL BELOW APPLICABLE EXPOSURE LEVELS.

Protective Gloves:NEOPRENE

Eye Protection:SPLASH SHIELDS

Work Hygienic Practices:WASH HANDS PROPERLY BEFORE EATING, SMOKING OR USING WASHROOM FACILITIES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323F/161.6C

Vapor Pres:2 MGHH@20C

Vapor Density:>1 (AIR=1)

Spec Gravity:1.392

Viscosity:77-89 KREBS

Evaporation Rate & Reference:0.12 (BU AC=1)

Solub

ility in Water:0%

Appearance and Odor:WHITE LIQUID ALIPHATIC ODOR

Percent Volatiles by Volume:39

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, OPEN FLAME.

Hazardous Decomposition Products:CO AND CO2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (pro

vided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.