

PRATT AND LAMBERT INC -- ENAMEL ALKYD GLOSS BROWN 10049 ID742006 -- 8010-00-298-2293
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS BROWN 10049 ID742006

MSDS Date:08/23/1990

FSC:8010

NIIN:00-298-2293

MSDS Number: BJLGH

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-13

61

Emergency Phone Num:716-873-6000 DOT EMER 8002553924

Preparer's Name:W.A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (VP 2 MMHG @ 20C)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 45%

Other REC Limits:LFL 1.0 UFL 7.0

OSHA PEL:100 PPM/525 MG/CU.M.

ACGIH TLV:100

PPM/525 MG/CU.M.

Ingred Name:VOC 3.94 LB/GAL LESS WATER & NPRS* 473 G/L LESS WATER
CALCULATED

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 10.10 LB/GAL SOLIDS 1212 G/L SOLIDS CALCULATED

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:REPORTS HAVE ASSOCIATED
PROLONGED/REPEATED OCCUPATIONAL OVEREXPOSURE TO
SOLVENTS WITH

PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY
DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL
OR FATAL.

Explanation of Carcinogenicity:NONE CURRENTLY KNOWN.

Effects of Overexposure:SWALLOW: CAN CAUSE GASTRO IRRIT, NAUSEA &
VOMITING. ASPIRATION INTO LUNGS MAY CAUSE CHEM PNEUMONITIS WHICH
CAN BE FATAL. INHALED:NOSE OR THROAT IRRIT. HIGH CONCENTRATE MAY
CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY
HEADACHE,

DIZZ, NAUSEA & CONFUSION. EYES: IRRIT. SKIN:MAY CAUSE
DEFATTING & IRRIT.

=====
===== First Aid Measures =====

First Aid:SWALLOW:DO NOT INDUCE VOMIT. CALL PCC/HOSPITAL/PHYSICIAN
IMMED. INHALED:REMOVE TO FRESH AIR IMMEDIATELY. IF BREATH STOPPED, GIVE
CPR. KEEP WARM/QUIET. GET MED ATTENTION IMMEDIATELY. EYES:FLUSH WITH H₂O, LIFTING
LIDS FOR 15 MINS. GET MED ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHES. WASH
AFFECTED AREA WITH SOAP & H₂O. OBTAIN MED ATTENTION IF IRRITATION PERSISTS.

NOTE
TO PHYSICIAN:DIRECT TREATMENT AT CONTROL OF SYMPTOMS & CLINICAL
CONDITIONS.

=====
===== Fire Fighting Measures =====

Flash Point:>102 F/>39 C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS DESIGNED FOR
FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:USE WATER TO COOL EXPOSED CONTAINERS TO
PREVENT PRESSURE BUILD-UP/AUTO-IGNITION/EXPLOSION FROM EXTREME HEAT.
IF WATER USED, FOG NOZZLES ARE PREFERRED

ERRABLE.

Unusual Fire/Explosion Hazard:OVEREXPOS TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY BE DELAYED, OBTAIN MED. KEEP CONTAIN TIGHTLY CLOSED. CONTAINER MAY EXPLODE FROM EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM IGNITE SOURCES. DIKE & CONTAIN W/MATERIAL(E.G. SAND,ETC)TRANSFER LIQ TO COVERED METAL CONTAIN FOR RECOVERY/DISPOSAL. REMOVE W/INERT ABSORB. USE ONLY NON-SPARK TOOLS. PREVENT CONTAM OF SEWERS,GROUNDWATERS W/MATERIAL/ABSORB
Neutralizing Agent:N/K.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 95F. STORE LARGE AMOUNTS IN COMPLIANCE W/OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.
Other Precautions:EMPTY CONTAINERS MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPT Y. DRUM IS NOT A PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELL VENTED AREA MAY NOT REQUIRE USE OF RSPRTR. RESTRICTED VENT:CHEM CARTRIDGE RSPRTR MAYBE REQUIRED. SPRAY:USE MECH PREFILTER. CONFINED AREA:USE AIR SUPPLIED RSPRTR. IF TLV EXCEED USE PROPERLY FITTED RSPRTR W/PROTECTION FACTOR

Ventilation:GEN DILUTE/LOCAL EXHAUST IN VOL/PATTERN TO KEEP CON CENTRATE

OF HAZARD INGRED BELOW LOWEST LIMITS. REMOVE DECOMP PRODUCTS

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING.

Supplemental Safety and Health

THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED AS HAZARDOUS WASTE BASED ON ITS IGNITABILITY CHARACTERISTIC, I.E. HAS A FLASH POINT OF 140 DEG. F. OR LE

SS. THE PROPER RCRA CLASSIFICATION WOULD BE D001.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:302 TO 390F
Vapor Density:> THAN AIR
Spec Gravity:1.0
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES
OF
IGNITION.
Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY
WELDING/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON
DIOXIDE.
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS, FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE &
LOCAL LAWS. INCINERATE ONLY EPA PERMITTED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPO
SAL OF
FLAMMABLE MATERIALS. CONTAMINATED ABSORB MAY BE DISPOSED IN HAZARD
WASTE LANDFILL

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.