

PRATT & LAMBERT INC., INDUSTRIAL COATING DIVISION -- ENAMEL ALKYD GLOSS GREEN 14064
ID 742412 -- 8010-00-298-2295

=====
Product Identification
=====

Product ID:ENAMEL ALKYD GLOSS GREEN 14064 ID 742412
MSDS Date:08/23/1990
FSC:8010
NIIN:00-298-2295
MSDS Number: BJLGJ
=== Responsible Party ===
Company Name:PRATT & LAMBERT INC., INDUSTRIAL COATING DIVISION
Address:16116 E. 13TH ST.
Box:2153
City:WIC
HITA
State:KS
ZIP:67201
Country:US
Info Phone Num:316-733-1361
Emergency Phone Num:316-733-1361
Preparer's Name:W.A. ELLISON
CAGE:PRATT
=== Contractor Identification ===
Company Name:PRATT & LAMBERT
Address:250 PETTIT AVE
Box:2153
City:BELLMORE
State:NY
ZIP:11710
Country:US
Phone:800-647-2253
CAGE:PRATT
Company Name:PRATT AND LAMBERT INC
Address:Box:6027
City:CLEVELAND
State:OH
ZIP:44101-1027
Country:US
Phone:216-566-2902
CAGE:61196

=====
Composition/Information on Ingredients
=====

=====

Ingred Name:MINERAL SPIRITS (VP 2 MMHG @ 20C)
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 50%
Other REC Limits:LFL 1.0 UFL 7.0
OSHA PEL:100 PPM/525 MG/UC.M.
ACGIH TLV:100 PPM/525 MG/CU.M.

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 102 F/>39 C
Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS DESIGNED FOR
FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:USE WATER TO COOL EXPOSED CONTAINERS TO
PREV
ENT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION FROM EXTREME HEAT.
IF WATER USED, FOG NOZZLES ARE PREFERRABLE.
Unusual Fire/Explosion Hazard:OVEREXPOS TO DECOMP PRODUCTS MAY CAUSE
HEALTH HAZARD. SYMPTOMS MAY BE DELAYED, OBTAIN MED. KEEP CONTAIN
TIGHTLY CLOSED. CONTAINER MAY EXPLODE FROM EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM IGNITE SOURCES.
DIKE & CONTAIN W/MATERIAL(E.G. SAND,ETC)TRANSFER
LIQ TO COVERED
METAL CONTAIN FOR RECOVERY/DISPOSAL. REMOVE W/INERT ABSORB. USE
ONLY NON-SPARK TOOLS. PREVENT CONTAM OF SEWERS,GROUNDWATERS
W/MATERIAL/ABSORB
Neutralizing Agent:N/K.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 95F. STORE LARGE
AMOUNTS IN COMPLIANCE W/OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY.
CLOSE CONTAINER AFTER EACH USE.
Other Precautions:EMPTY CONTAINERS MUST NOT BE WASHED & RE-

USED FOR ANY

PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPT Y. DRUM IS NOT A PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELL VENTED AREA MAY NOT REQUIRE USE OF RSPRTR.

RESTRICTED VENT:CHEM CARTRIDGE RSPRTR MAYBE REQUIRED. SPRAY:USE MECH PREFILTER. CONFINED AREA:USE AIR SUPPLIED RSPRTR. IF TLV EXCEED USE PROP

ERLY FITTED RSPRTR W/PROTECTION FACTOR

Ventilation:GEN DILUTE/LOCAL EXHAUST IN VOL/PATTERN TO KEEP CONCENTRATE OF HAZARD INGRED BELOW LOWEST LIMITS. REMOVE DECOMP PRODUCTS

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING.

Supplemental Safety and Health

THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED AS HAZARDO US

WASTE BASED ON ITS IGNITABILITY CHARACTERISTIC, I.E. HAS A FLASH POINT OF 140 DEG. F. OR LESS. THE PROPER RCRA CLASSIFICATION WOULD BE D001.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:302 TO 390F

Vapor Density:> THAN AIR

Spec Gravity:1.0

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:62

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ST

ONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS, FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY

EPA PERMITTED FACILITY. DO NOT

INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF
FLAMMABLE MATERIALS. CONTAMINATED ADSORBENT MAY BE DISPOSED IN HAZARD
WASTE LANDFILL

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for

its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.