

CHEMICAL SPECIALISTS & DEVELOPMENT -- THINNER, PAINT TYPE III - ODORLESS --
8010-00-837-7969

===== Product Identification =====

Product ID:THINNER, PAINT TYPE III - ODORLESS

MSDS Date:09/01/1990

FSC:8010

NIIN:00-837-7969

MSDS Number: BJLKC

=== Responsible Party ===

Company Name:CHEMICAL SPECIALISTS & DEVELOPMENT

Address:#5 HACKBERRY LANE

City:CUT & SHOOT

State:TX

ZIP:77303

Country:US

Info Phone N

um:409-756-1065

Emergency Phone Num:800-424-9300

CAGE:CHEMS

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS INC

Address:149 WEST TRIGG AVE

City:HARRISBURG

State:NC

ZIP:28075

Country:US

Phone:704-522-0825

CAGE:CHEMS

Company Name:CSD INC. (PRE 1985 NAME: MATHEWS, INC)

Address:420 SEABOARD DRIVE

Box:City:MATTHEWS

State:NC

ZIP:28105-5073

Country:US

Phone:704-821-9822

CAGE:5W216

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT

CAS

:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:OVEREXPOSURE TO EYES MAY CAUSE
IRRITATION, REDNESS, TEARING, BLURRED VISION. OVEREXPOSURE TO SKIN
MAY CAUSE IRRITATION, DEFATTING & DERMATITIS. INHALATION
MAY CAUSE
NASAL & RESPIRATORY IRRITATION. ASP IRATION OF MATERIAL INTO LUNGS
MAY CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Overexposure:DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE,
POSSIBLE UNCONSCIOUSNESS, ASPHYXIATION, AND IRRITATION TO PARTS OF
THE BODY WITH DIRECT CONTACT.

=====
===== First Aid Measures =====

===

First Aid:EYES: FLUSH W/PLENTY OF WATER, LIFTING LIDS OCCAS, GET MED
ATTN. SKIN: WASH THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED
CLOTHES. WASH CLOTHES BEFORE RE-USE. IF SWALLOWED, DO NOT INDUCE
VOMITING. KE EP PERSON WARM, QUIET & GET MED ATTN. IF BREATHED:
MOVE TO FRESH AIR. IF BREATHING DIFFICULT, GIVE OXYGEN. IF
BREATHING STOPPED, GIVE CPR. GET MEDICAL ATTN IMMEDIATELY FOR ANY
OF THESE CONDITIONS.

=====
===== Fire Fighting Measures =====

=====

Flash Point Method:TCC
Flash Point:140F/60C
Lower Limits:1.0 VOL
Upper Limits:6.0 VOL
Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH
FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE
PRESSURE MODE WHEN FIGHTING FIRES.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL
ALONG GROUND OR BE MOVED BY VENTILATION & IGNITED BY HEAT OR OTHER
IGNITE SOURCES AT LO

CATIONS DISTANT FROM MATERIAL.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITE SOURCES, KEEP SPECTATORS AWAY, STOP SPILL AT SOURCE, DIKE AREA, PREVENT SPREADING, PUMP LIQ TO SALVAGE TANK. TAKE UP REMAINDER W/SAND, CLAY, EARTH, FLOOR ABSORB & SHOVEL TO CONTAINERS. PREVENT CONTAMINATION OF GROUND WATER.

===== Handling and Storage =====

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS MUST BE OBSERVED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV OF PRODUCT IS EXCEEDED, USE A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR OR OTHER NIOSH/MSHA APPROVED RESPIRATOR UNDER SPECIFIED CONDITIONS. ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

Ventilation:PROVIDE SUFFICIENT MECHANICAL GENERAL & OR LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLVS.

Protective Gloves:RESISTANT GLOVES, NITRILE RUBBER.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Work Hygienic Practices:WEAR IMPERVIOUS CLOTHING & BOOTS.

Supplemental Safety and Health

NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:360F - 182C

Melt/Freeze Pt:M.P/F.P Text:-20F,-29C

Vapor Pres: .05 MM HG

Vapor Density:5.17

Spec Gravity:0.740

Evaporation Rate & Reference:ETHYL ETHER = 1).03

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, LITTLE IF ANY COLOR; SLIGHT OIL ODOR

Percent Volatiles by Volume:100

Corrosion Rate:NOT CORR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG

OXIDIZING AGENTS.

Hazardous Decomposition Products: MAY FORM TOXIC MATERIALS:, CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE, & FEDERAL REGULATIONS. SMALL SPILLS: ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD. WAIT FOR VAPORS TO CLEAR COMPLETELY FROM HOOD DUCT WORK. LARGE SPILLS: DESTROY BY LIQUID INCINERATION.

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.