

SHERWIN INC -- ER83A EMULSIFIER (HYDROPHILIC) -- 6850-01-263-8227

===== Product Identification =====

Product ID:ER83A EMULSIFIER (HYDROPHILIC)

MSDS Date:01/01/1987

FSC:6850

NIIN:01-263-8227

Kit Part:Y

MSDS Number: BJLMK

=== Responsible Party ===

Company Name:SHERWIN INC

Address:5530 BORWICK AVE

City:SOUTH GATE

State:CA

ZIP:90280-7402

Country:US

Info Phone Num:213-861-6324

Emergency Phone Num:213-

861-6324

CAGE:21405

=== Contractor Identification ===

Company Name:SHERWIN INC.

Address:5530 BORWICK AVE.

City:SOUTH GATE

State:CA

ZIP:90280-7402

Country:US

Phone:562-861-6324/FAX 923-8370

CAGE:21405

===== Composition/Information on Ingredients =====

Ingred Name:NONIONIC SURFACTANTS

Fraction by Wt: 30 - 60%

Other REC Limits:NONE SPECIFIED

Ingred Name:GLYCOLS

Fraction by Wt: 30 - 60%

Other REC Limits:NONE SPECIFIED

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction b

y Wt: 0.5 - 4%

Other REC Limits:NONE SPECIFIED

Ingred Name:DYESTUFF

Fraction by Wt: 200F,>93C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====

= Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL FLAMES. CONTAIN SPILLED MATERIAL. SOAK UP WITH ABSORBENT MATERIAL AND PLACE INTO LEAK PROOF CONTAINERS FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:NONE SPECIFIED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF VAPORS OR MISTS ARE GENERATED, USE A NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION TO PREVENT OVEREXPOSURE.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO MINIMIZE EXPOSURE. LOCAL EXHAUST RECOMMENDED BY MANUFACTURER.

Protective Gloves:NEOPRENE, BUTYL

Eye

Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T6

Boiling Pt:B.P. Text:390F,199C

Evaporation Rate &

; Reference:0.1 (BUTYL ACETATE = 1)
Solubility in Water:APPRECIABLE
Appearance and Odor:PINK LIQUID, DETERGENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OTHER
INCOMPLETELY BURNED CARBON PRODUCTS.

===== Disposal Considerations =====
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.