

PRATT AND LAMBERT INC -- LAC. ACR. WHITE 17875 AM ID 794716 -- 8010-00-935-6608

=====  
Product Identification  
=====

Product ID:LAC. ACR. WHITE 17875 AM ID 794716

MSDS Date:12/11/1990

FSC:8010

NIIN:00-935-6608

MSDS Number: BJMFX

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergen

cy Phone Num:873-6000 DOT EMER 8002553924

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CYCLOHEXANONE (VAPOR PRESSURE 2 MM HG @ 20C) (SKIN) (LFL:  
1.1)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACGIH T

LV:S, 25 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 15%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:METHYL ETHYL KETONE (SARA 313) (VAPOR PRESSURE 70  
MM HG @  
20C) (LFL: 2.0 UFL: 10.0)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 20%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/300 PPM STEL  
ACGIH TLV:200 PPM/300 PPM STEL  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (SARA 313) (LFL: .3)  
CAS:85-68-7  
RTECS #:TH9990000  
Fraction by Wt: < 5%  
Other REC Limits:NONE SPECIFIED  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:ISOPROPYL ALCOHOL (VAPOR PRESSURE 33 MM HG @ 20F) (LFL: 3.0  
UFL: 13.0)  
CAS:67-6

3-0  
RTECS #:NT8050000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM/500 PPM STEL  
ACGIH TLV:400 PPM/500 PPM STEL

Ingred Name:VOC: 4.96 LB/GL LESS WATER & NPRS\*; 595 G/L LESS WATER;  
CALCULATED \*NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 16.21 LB/GAL SOLIDS; 1945 G/L SOLIDS; CALCULATED  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INGEST/INHALE/EYE/SKIN: IRRITATION  
(GASTROINTESTINAL, NOSE, THROAT, EYE, SKIN). LUNG ASPIRATION MAY  
CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. CENTRAL NERVOUS  
SYSTEM DEPRESSION. CORNEAL DAMAGE. S KIN ABSORPTION. OVEREXPOSURE:  
LIVER DAMAGE. PERIPHERAL NEUROPATHY, PERMANENT BRAIN AND NERVOUS  
SYSTEM DAMAGE.

Effects of Overexposure  
:INGEST: NAUSEA/VOMITING. INHALE: HEADACHES,  
DIZZINESS, NAUSEA, CONFUSION.

Medical Cond Aggravated by Exposure:TOLUENE HAS BEEN FOUND TO CAUSE  
KIDNEY, LUNG & SPLEEN DAMAGE IN LAB ANIMALS. LAB STUDIES INVOLVING  
RATS INDICATE SOME EVIDENCE THAT METHYL ETHYL KETONE MAY BE  
EMBRYOTOXIC, FETOTOXIC AND TERATOGENIC.

=====  
First Aid Measures  
=====

First Aid:INGEST: DO NOT INDUCE VOMITING. CALL POISON CONTROL,  
EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY. INHALE: REMOVE TO FRESH  
AIR IMMEDIATELY. GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM &  
QUIET. GET IMMEDIATE MEDICAL AID. EYE: FLUSH THOROUGHLY WITH LARGE  
AMOUNT OF WATER FOR 15 MIN. GET MEDICAL AID. SKIN: REMOVE  
CONTAMINATED CLOTHES. WASH AFFECTED AREA WITH SOAP & WATER.  
PERSISTANT IRRIT GET MED AID.

=====  
Fire Fighting Measures  
=====

Flash Point:24.0F,-4.4C  
Lower Limits:.3  
Upper Limits:13.0  
Extinguishing Media:USE NFPA CLASS B(C)

O2, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) FOR LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, USE TO COOL CONTAINERS (FOG NOZZLE PREFERABLE) TO PREVENT PRESSURE BUILD-UP & AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE SOURCES. DIKE, CONTAIN & REMOVE WITH INERT MATERIAL (SAND, EARTH, ETC). USE COVERED METAL CONTAINERS FOR RECOVERY AND DISPOSAL. USE NON-SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS & GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. LARGE QUANTITY STORAGE: COMPLY WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CONTAINERS TO BE CLOSED AFTER USE.

Other Precautions:DO NOT REUSE CONTAINERS FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED AREA: NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR. SPRAYING: MECHANICAL PREFILTER MAY BE REQUIRED. CONFINED AREAS: NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. EXCEEDED TLV AREA: NIOSH/MSHA APPROVED RESPIRATOR W/RIGHT FACTOR.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN TO KEEP CONCENTRATIONS BELOW EXPOSURE LIMITS.

Protective Gloves:REPEAT/PROLONG USE: IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Supplements

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 698F

Vapor Density:> AIR

Spec Gravity:1.1

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Solubility in Water:NA

Appearance and Odor:PAINT

Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESS

HEAT(>100F) & IGNITION

SOURCES.

Hazardous Decomposition Products:BURNING,INCLUDING HEATED BY WELDING OR CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE & CARBON DIOXIDE, POSSIBLE NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS & LAWS. INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. USE PRECAUTIONS FOR DISPOSAL OF HAZARDOUS MATERIAL-D001. USE HAZARDOUS WA STE LANDFILL FOR USED ABSORBENT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.