

DOW CORNING CORP -- MOLYKOTE(R) 44 GREASE-ALL GRADES -- 9150-01-014-3512
===== Product Identification =====

Product ID:MOLYKOTE(R) 44 GREASE-ALL GRADES

MSDS Date:01/19/1981

FSC:9150

NIIN:01-014-3512

Kit Part:Y

MSDS Number: BJMGT

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Eme

rgency Phone Num:517-496-5900

Preparer's Name:L.C. VANVOLKINBURG

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:NOT HAZARDOUS INGRE

DIENTS

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:ACUTE-EYES:MAY CAUSE TEMPORARY DISCOMFORT.CHRONIC-NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:MAY CAUSE TEMPORARY DISCOMFORT TO EYES.

Medical Cond Aggra

vated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:>250F,>121C

Extinguishing Media:CARBON DIOXIDE OR FOAM

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING

CHEMICAL FIRE. USE WATER

SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS GREASE. USE ABSORBENT MATERIAL TO COLLECT THE REST AND CONTAIN FOR SALVAGE OR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN

A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM OPEN FLAMES & HIGH TEMPERATURES.

Other Precautions:MINIMIZE SKIN CONTACT. WASH WITH SOAP & WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES (SHOES) THAT CAN NOT BE DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATORY PROTECTION NOT ORDINARILY REQUIRED.

Ventilation:MECHANICAL

Protective Gloves:NEOPRENE RUBBER AS REQUIRED.

Eye Protection:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

KIT CONSISTS OF PART N

OS. 39479-P8,39479-P9,39479-P15, AND

39479-P16.ACTION INITIATED TO CANCEL SUBJECT NSN. NO FURTHER BUYS SHOULD BE MADE.MANUFACTURER HAS DISCONTINUED MARKETING ITEMS AS A KIT.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres: