View NSN Online: https://aerobasegroup.com/nsn/8010-01-066-5635

Product ID:ICC MAT COATINGS

MSDS Date:01/01/1987

FSC:8010

NIIN:01-066-5635

MSDS Number: BJMHR === Responsible Party ===

Company Name: INTERNATIONAL COATINGS CO

Address:13929 F 166TH ST

City:CERRITOS

State:CA ZIP:90701 Country:US

Info Phone Num:213-926-0747

Emergency Phone Num:213-926-0747

CAGE:INCM

Μ

=== Contractor Identification ===

Company Name: EXPANDED RUBBER AND PLASTIC CORP

Address:14000 S WESTERN AVE

Box:City:GARDENA

State:CA

ZIP:90249-3008 Country:US

Phone:310-321-4260

CAGE:25598

Company Name: INTERNATIONAL COMMUNICATION

Address: ROUTE 119 SOUTH

Box:386

City:CONNELLSVILLE

State:PA ZIP:15425 Country:US

Phone:412-628-1014;800-424-9300(CHEMTREC)

CAGE:INCMM

====== Composition/Information on Ingredients ========

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 50%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000 Fraction by Wt: 6% OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

=========== Hazards Identification ==========================

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: VAPOR IRRITATES EYES, NOSE & THROAT.

LIQUID WILL DAMAGE EYE TISSUES. LIQUID IS IRRITATING TO SKIN

CAUSING DERMATITIS.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:INHAL:REMOVE TO FRESH AIR. SEE MD. SKIN:WASH THOROU GHLY WITH

SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES. CALL MD. INGEST:GET MD IMMED .

============ Fire Fighting Measures =========================


Flash Point Method:TCC Flash Point:21.0F,-6.1C

Lower Limits:1.8 Upper Limits:10.0

Extinguishing Media:DRY CHEMICAL, CO*2 OR MECHANICAL FOAM

Fire Fighting Procedures: USE WATER SPRAY TO COOL SURROUNDING MATERIALS AND SURFACES. NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT REQUIRED FOR FIRE FIGHTING PERSONNEL.

Unu



COLORS Percent Volatiles by Volume:80-90%

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:EXPOSURE TO HIGH HEAT, OPEN FLAMES, SPARKS Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, HYDROGEN CHLORIDE.

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE OR DISPOSE OF I/A/W FEDERAL, STATE AND LOCAL REGULAT IONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.