

CAAP CO INC -- POLYURETHANE CURING AGENT -- 8010-01-242-8160

===== Product Identification =====

Product ID:POLYURETHANE CURING AGENT

MSDS Date:06/28/1988

FSC:8010

NIIN:01-242-8160

Kit Part:Y

MSDS Number: BJMKQ

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-877-0375

Emergency Phone Num:203-877-0375

Pre

parer's Name:RONALD D. ARENA

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC AMINE, NAME WITHHELD AS A TRADE SECRET

Other REC Limits:10 PPM REC BY MFGR

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Other REC Limits:75 PPM STEL

OSHA PEL:100 PPM/75 S

TEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CONTACT CORROSIVE TO EYES; SKIN IRRITANT, MAY CAUSE BURNS OR RASH. INHALATION: UPPER RESPIRATORY IRRITATION, MAY BE TOXIC IN VERY HIGH DOSES. CHRONIC: WEIGHT LOSS, ANEMIA, LIVER, KIDNEY, POSSIBLE SIB LE SPLEEN DAMAGE. POSSIBLE SENSITIZER. ROUTES OF INHALATION AND POSSIBLE SIGNIFICANT SKIN PENETRATION.
Explanation of Carcinogenicity:THE PRODUCT GAVE NEGATIVE AMES SCREEN TEST RESULTS; NONE OF THE INGREDIENTS ARE LISTED AS CARCINOGENS.
Effects of Overexposure:PUNGENT ODOR, UPPER RESPIRATORY IRRITATION, EYE IRRITATION, TEARING, BLURRING OF VISION AND HEADACHE.
Medical Cond Aggravated by Exposure:PRE-EXISTING LIVER DISEASE MAY BE AGGRAVATED.

=====
First
Aid Measures
=====

First Aid:EYES: FLUSH WITH LUKE WARM WATER 15 MINUTES AND CALL DOCTOR.
SKIN: WASH WITH SOAP AND WATER; IF IRRITATION PERSISTS, CALL DOCTOR. INHALATION: REMOVE TO FRESH AIR; CALL DOCTOR; GIVE ARTIFICIAL RESPIRAT ION IF NOT BREATHING. INGESTION: CALL DOCTOR.

=====
Fire Fighting Measures
=====

Flash Point Method:TOC
Flash Point:74 F/23 C
Lower Limits:0.9
Upper Limits:7.5
Extinguishing Media:DRY CHEMICAL, CO2, FOAM.
Fire Fighting Procedures:USE FULL PROTECTIVE GEAR, INCLUDING SCBA AND RUBBER OR OTHER CHEMICAL PROTECTIVE SUIT FOR AMINE/AMMONIA TYPE CORROSIVE VAPORS.
Unusual Fire/Explosion Hazard:NONE. FLAMMABLE LIQUID AND CORROSIVE LIQUID WHEN WATER ADDED.

=====
Accidental Release Measures
=====

Spill Release Procedures:DIKE SPILL AND SOAK UP WITH ABSORBANT MATERIAL. USE PROTECTIVE GLOVES, MASK, GOGGLES AND APRON. PLACE IN TIGHTLY SEALED CONTAINERS

=====

==== Handling and Storage =====

Handling and Storage Precautions:KEEP IGNITION SOURCES AWAY. KEEP CONTAINERS CLOSED WHEN NOT IN USE. STORE IN A COOL, DRY PLACE.
Other Precautions:DO NOT BREATHE VAPOR OR MIST. AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED SPECIAL CARBON CANNISTER, SCBA OR SUPPLIED AIR FOR EMERGENCY USE.
Ventilation:LOCAL:YES;MAINTAIN MIBK CONCENTRATE BELOW 10PPM.
MECH(GEN):CONCENTRATE MIX WELL BELOW TLV. SPECIAL:SPRAY BOOTH IF INDOOR
Protective Gloves:NEOPRENE OR POLYETHYLENE
Eye Protection:SPLASH-PROOF GOGGLES, SOLVENT RESISTANT
Other Protective Equipment:RUBBER OR POLYETHYLENE APRON, EMERGENCY EYE WASH AND SHOWER.
Work Hygienic Practices:WASH HANDS AFTER USE. KEEP AREA NEAT AND CLEAN.
Supplemental Safety and Health
KEY1:F4.

==== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:231 TO 266F
Vapor Pres:3
Vapor Density:3.7
Spec Gravity:0.83 (H2O=1)
Evaporation Rate & Reference: