View NSN Online: https://aerobasegroup.com/nsn/9150-00-180-6290 HULS AMERICA INC -- MIL-H-83282C; LUBRICANT -- 9150-00-180-6290 ============= Product Identification =============== Product ID:MIL-H-83282C;LUBRICANT MSDS Date:02/10/1989 FSC:9150 NIIN:00-180-6290 MSDS Number: BJMXC === Responsible Party === Company Name: HULS AMERICA INC Address:80 CENTENNIAL AVE Box:456 City:PISCATAWAY State:NJ ZIP:08855-0456 Country:US Info Phone Num:201-763-7173 Emergency Phone Num:201-763-7173 CAGE:63182 === Contractor Identification === Company Name: HULS AMERICA INC Address:TURNER PLACE Box:365 City:PISCATAWAY State:NJ ZIP:08855 Country:US Phone:201-763-7173 CAGE:63182 ======= Composition/Information on Ingredients ========

Ingred Name: SYNTHETIC HYDROCARBONS


Fraction by Wt: 100.0%

Other REC Limits: NONE SPECIFIED

========== Hazards Identification =============

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES

Reports of Carcinogenicity



RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF AILMENTS

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE

VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

Flash Point Method:COC Flash Point:410F,210C Lower Limits:1.0 Upper Limits:6.0

OR WITH A PRE-EXISTING DISE ASE INVOLVING THE EYES, SKIN, OR

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTA

INERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard: CONTAINERS MAY EXPLODE DUE TO EXTREME HEAT. FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

	Accidental Release Measures	
--	-----------------------------	--

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; CONTAIN FREE MATERIAL IF POSSIBLE; USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL IN AN APPROVED CONTAINER.

Neutralizing Agent: NOT APPLICABLE.

\_\_\_\_\_

====== Handling and Storage	
-----------------------------	--

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves: NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection: SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTA

MINATED CLOTHING OR

FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

========= Physical/Chemical Properties ===========

HCC:V6
Boiling Pt:B.P. Text:520F,271C
Vapor Pres:0.02
Vapor Density:>1.0
Spec Gravity: