

AKRON PAINT AND VARNISH INC -- TYPE II WALKWAY DARK GULL GRAY, G-8130 --
8010-00-641-0426

===== Product Identification =====

Product ID:TYPE II WALKWAY DARK GULL GRAY, G-8130

MSDS Date:07/26/1990

FSC:8010

NIIN:00-641-0426

MSDS Number: BJMZH

=== Responsible Party ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PKY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Info Phone Num:330

-773-8911

Emergency Phone Num:330-773-8911

CAGE:70228

=== Contractor Identification ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETR.DISTILLATES (VP 15 MM HG) (THAN AIR MAY TRAVEL BY GROUND,ETC.

TO IGNITE SOURCE DISTANT FROM HANDLING POINT.CONTAIN(EMPTY)MAY EXPLODE.OVEREXP TO DECOMP, POSSBL DELAYED HEALTH HAZARD

===== Accidental Release Measures =====

Spill Release Procedures:SM:ABSORB LIQ W/RAGS,ABSORB,VERMICUL,OTHER & TRANSFER TO HOOD. LG:ELIM IGNITE SOURCES.DIKE AREA.VENT AREA,PUMP LIQ INTO SALVAGE TANK,REMAIN LIQ TAKE UP W/SAND,FLOOR ABSORB,OTHER ABSORB & SHOVEL INTO C ONTAINER. PREVENT RUN-OFF TO SEWERS & BODIES OF*

Neutralizing Agent:N/K. *WATER. NOTIFY PROPER AUTHORITIES AS REQUIRED BY LOCAL,STATE & FED REGS.

=====

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT DROP CONTAIN.AVOID HEAT,SPARK,OPEN FLAME. STORE LG AMNT ONLY IN BLDG DESIGNED TO COMPLY W/OSHA1910.106.NEVER USE PRESS TO EMPTY.AVOID INHALING.
Other Precautions:HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED WITH AIR. IGNITION MAY OCCUR AT TEMPERATURES BELOW THOSE PUBLISHED IN THE LITERATURE AS "AUTOIGNITION" OR "IGNITION" TEMPERAT URES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IF OUTDOORS OR OPEN AREAS WITH UNRESTRICTED VENTILATION APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICULATES & VAPORS. IN CONFINED AREAS, APPROVED AIR LINE TYPE RESPIR ATORS OR HOODS.

Ventilation:PROVIDE SUFF VENT IN VOL/PATTERN TO KEEP AIR CONTAM CONCENTRATE BELOW CURRENT APPLICABLE LIMITS. REMOVE DECOMP PRODUCTS.

Protective Gloves:RESISTANT GLO VES SUCH AS NITRILE RUBBER

Eye Protection:CHEM SPLASH GOGGLES OR OTHERS PERMITTED

Other Protective Equipment:NORMAL PROTECTIVE CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:OBSERVE ALL PRECAUTIONS. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

CAUTION: THIS PRODUCT CONTAINS PIGMENTS WHICH MAY BECOME A DUST NUISANCE WHEN REMOVED BY SANDING, ABRADING OR SANDBLASTING. DUST MASKS SHOULD BE WORN DURING THESE OPERATIONS TO AVOID THI S HAZARD.

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:240 TO 285F

Vapor Density:> THAN AIR

Spec Gravity:1.35

Evaporation Rate & Reference:6.87 X N-BUTYL ACETATE

Appearance and Odor:DARK GULL GRAY LIQUID.

Percent Volatiles by Volume:50.7

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZERS (E.G. NITRIC ACID)

Stability Condition to Avoid:KEEP AW

AY FROM HEAT AND OPEN FLAME.

Hazardous Decomposition Products:MAY FORM CARBON MONOXIDE AND DIOXIDE,
VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whats
oever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.