View NSN Online: https://aerobasegroup.com/nsn/8010-00-165-8627

TRIAD PAINT AND CHEMICAL CORP. -- TT-S-711C -- 8010-00-165-8627

Product ID:TT-S-711C MSDS Date:01/01/1987 FSC:8010 NIIN:00-165-8627 MSDS Number: BJNJH === Responsible Party === Company Name: TRIAD PAINT AND CHEMICAL CORP. Address:810 EVERGREEN AVENUE City:BROOKLYN State:NY ZIP:11207 Country:US Info Phone Num:718-443-2778 Emergency Phone Num:718-443-2778 CAGE:3315 1 === Contractor Identification === Company Name: STEVEN INDUSTRIES Address:39 AVENUE C Box:8 **City:BAYONNE** State:NJ ZIP:07002-3417 Country:US Phone:201-437-6501 CAGE:33150 Company Name: TRIAD PAINT AND CHEMICAL CORP Address:810 EVERGREEN AVE Box:City:BROOKLYN State:NY ZIP:11207-1140 Country:US CAGE:33151

Ingred Name:PIGMENTS Fraction by Wt: 6.6% * Other REC Limits:* % WT. STAIN

Ingred Name:VEHICLE Fraction by Wt: 93.4% * Other REC Limits:* % WT. STAIN

Ingred Name:SOLVENTS Fraction by Wt: 62.4% * Other REC Limits:* % WT. STAIN ACGIH TLV:100 PPM

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Health Hazards Acute and Chronic:VAPORS MIGHT BE IRRITATING TO EYES, NOSE AND THROAT. REPEATED EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE, DIZZINESS, SLEEPINESS AND NAUSEA. DEFATTING TO SKIN. Effects of Overexposure:VAPORS MIGHT BE IRRITATING TO EY ES, NOSE AND

THROAT. REPEATED EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE, DIZZINESS, SLEEPINESS AND NAUSEA. DEFATTING TO SKIN.

First Aid:INHALATION: PROVIDE FRESH AIR AND REST. SKIN CONTACT: WASH WITH MILD SOAP AND WATER. USE EMOLLIENT CREAM OR LOTION. EYE CONTACT: WASH WITH A GENTLE STREAM OF WATER FOR 10 MINUTES. SEE A DOCTOR.

Flash Po int Method:PMCC Flash Point:105 F/41 C Lower Limits:1.0 Upper Limits:6.0 Extinguishing Media:FOAM, CO2, DRY CHEMICALS. Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED RESPIRATORS. WATER STREAM WILL SPREAD OIL FIRES. Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE FROM HOT METAL SURFACES AND OTHER SOURCES OF IGNITION. VAPOR FORMS EXPLOSIVE MIXTURE BETWEEN UPPER AND LOWER EXPLOSIVE UNITS.

Spill R

elease Procedures: AVOID FLAME AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. WIPE UP SPILL WITH INERT ABSOBENT(S) AND NON-SPARKING TOOLS. SAFELY DISCARD SATURATED ABSORBENTS(S). AVOID PROLONGED BREATHING OF VAPORS WH ILE CLEANING UP SPILL. Handling and Storage Precautions: AVOID OPEN FLAME AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT. Other Precautions: DO NOT TAKE INTERNALLY, AVOID PRO LONGED OR REPEATED CONTACT WITH SKIN. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. Respiratory Protection: ORGANIC CANNISTER MASK OR AIR PACK IF VENTILATION IS IN ADEQUATE. Ventilation: MECHANICAL: WITH APPROVED CLASS D EXPLOSION PROOF MOTOR AND SWITCHES. Protective Gloves: NEOPRENE RUBBER GLOVES. Eye Protection: CHEMICAL SAFETY GOGGLES. Supplemental Safety and Health ================= Physical/Chemical Properti es =================================

HCC:F4 Boiling Pt:B.P. Text:315F,157C Vapor Pres:1 @ 100 F Vapor Density:5.0 Spec Gravity:.901 (H2O=1) Evaporation Rate & amp; Reference:.13 (N-BUTYL ACETATE=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:MAHOGANY COLORED LIQUID. HYDROCARBON ODOR. Percent Volatiles by Volume:72

Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZING AGENTS. Hazardous Decomposition Products:CO, CO2, ACRID

Waste Disposal Methods:DISPOSAL PROCEDURES MUST COMPLY WITH LOCAL, STATE AND FEDERAL REGULATION.

09JAN91

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this infor mation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.