

PERMAGILE INDUSTRIES INC -- INSULCAST 165 LV PART B, IC-0165-087500-B -- 8030-00-229-8740

=====  
Product Identification  
=====

Product ID:INSULCAST 165 LV PART B, IC-0165-087500-B

MSDS Date:10/03/1990

FSC:8030

NIIN:00-229-8740

Kit Part:Y

MSDS Number: BJNKB

==== Responsible Party ====

Company Name:PERMAGILE INDUSTRIES INC

Address:101 COMMERCIAL ST

City:PLAINVIEW

State:NY

ZIP:11803

Country:US

Info Phon

e Num:516-349-1100 DAY;800-645-7546 OTHER

Emergency Phone Num:800-424-9300

Preparer's Name:LAWRENCE T. DEMAIO

CAGE:13549

==== Contractor Identification ====

Company Name:PERMAGILE INDUSTRIES INC

Address:101 COMMERCIAL STREET

City:PLAINVIEW

State:NY

ZIP:11803

Country:US

Phone:516-349-1100/800-424-9300(CHEMTREC)

CAGE:13549

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MODIFIED ALIPHATIC AMINE (VAPOR PRESSURE 1.0 MM HG @ 20C)

Fraction by Wt: 100%

Other REC Limits:

LEL 1.4

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:RAT ORAL 3000

Health Hazards Acute and Chronic:EYES: IRRITATION, BLINDNESS OR

PERMANENT EYE INJURY. SKIN: SEVERE IRRITATION, SENSITIZATION AND ALLERGIC RESPONSES. INHALATION: IRRITATION TO RESPIRATORY TRACT, HEADACHE, DIZZINESS, NAUSEA AND VOMITIN G.

=====  
First Aid Measures  
=====

First Aid:MOVE TO FRESH AIR. ARTIFICIAL RESPIRATION IF NECESSARY. WAS

H

SKIN WITH SOAP AND WATER OR WATERLESS HAND CLEANER. REMOVE CONTAMINATED CLOTHING. DO NOT INDUCE VOMITING. DRINK LARGE QUANTITIES OF WATER OR MILK MIXED WITH SALT. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. FLUSH EYES WITH WATER FOR 15 MIN.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:259F,126C

Lower Limits:1.4

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting

Procedures:USE SELF-CONTAINED BREATHING APPAR & PROTECT CLOTHING.WATER FOG TO COOL CONTAINERS. SHUT OF ALL VALVES & POWER TO AREA. USE EMERG LIGHTS. BE SAFE DISTANCE AWAY.

Unusual Fire/Explosion Hazard:IRRITATING AND/OR TOXIC GASES MAY BE PRESENT.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE/ABSORB W/SAND & DISPOSE IN APPR'D MANNER. REMOVE ALL IGNITE SOURCES. WEAR PROTECT CLOTHES. STOP FROM ENTERING UNDERGROUND WATER SYS.

FLUSH AREA/NOT TO SEWER. VENTILATE AREA.

EMULIFY RESIDUE W/SOA P/WATER,ABSORB. ABSORBENT IN DRY DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT FREEZE. RUPTURES WHEN OVERHEATED. KEEP IN COOL, DRY PLACE, FROM IGNITE SOURCES & FOOD. KEEP CLOSED WHEN NOT USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID BREATHING FUMES, MISTS, VAPORS. NESA/NIOSH APPROVED RESPIR

ATOR RECOMMENDED. SELF-CONTAINED BREATHING APPARATUS IN CONCENTRATIONS ABOVE PEL/TLV.

Ventilation:ADEQUATE CROSS AIR CIRCULATION. EXHAUST AT POINT OF USE. MECHANICAL IN CONFINED AREAS.

Protective Gloves:RUBBER OR NEOPRENE.

Eye Protection:SPLASHPROOF SAFETY GLASSES/GOGGLES.

Other Protective Equipment:EYEWASH, EMERGENCY SHOWER, CHEMICAL APRON, RUBBER FOOT COVERING, CLEAN LONG SLEEVE & LEG CLOTHING.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING,

SMOKING OR USING TOILET. USE OF BARRIER CREAM  
RECOMMENDED.

Supplemental Safety and Health

CHECK ALL CONTAINERS FOR LEAKS. AVOID PROLONGED BREATHING OR CONTACT  
WITH SKIN.

===== Physical/Chemical Properties =====

Spec Gravity:.95

Evaporation Rate & Reference:SLOWER: N-BUTYL ACETATE

Solubility in Water:NEGLIGIBLE (