

HULS AMERICA INC -- MIL-H-17672D (2110TH) -- 9150-00-753-4799

=====
Product Identification
=====

Product ID:MIL-H-17672D (2110TH)

MSDS Date:01/16/1989

FSC:9150

NIIN:00-753-4799

MSDS Number: BJNML

=== Responsible Party ===

Company Name:HULS AMERICA INC

Address:80 CENTENNIAL AVE

Box:456

City:PISCATAWAY

State:NJ

ZIP:08855-0456

Country:US

Info Phone Num:201-980-6800

Emergency Phone Num:201-980-6800

P

reparer's Name:P.A. PARKER

CAGE:63182

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: 7%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:PETROLEUM HYDROCARBON MIXTURE

Fract

ion by Wt: 93%

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INGESTION: NOT NORMALLY

EXPECTED TO CAUSE ANY ILL EFFECTS. INHALATION: NO SIGNIFICANT
ADVERSE HEALTH EFFECTS ARE EXPECTED FOR SHORT TERM EXPOSURE. EYE:
NOT NORMALLY EXPECTED TO CAUSE ANY ILL EF FECTS. SKIN: NOT NORMALLY

EXPECTED TO CAUSE ANY ILL EFFECTS. CHRONIC: PROLONGED/REPEATED
CONTACT MAY CAUSE IRRITATION.

Explanation of Carcinogenicity:THE COMPONENTS OF THIS PRODUCT HAVE NOT
SHOWN ANY EVIDENCE OF BEING CARCINOGENIC.

Effects of Overexposure:OVEREXPOSURE MAY LEAD TO RESPIRATORY
IRRITATION, DERMATITIS AND EYE IRRITATION. MISTS OR FUMES FROM
EXCESSIVE HEATING MAY CAUSE EYE AND SKIN IRRITATION, NAUSEA,
VOMITING, RESPIRATORY TRACT IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH
A SKIN DISORDER SHOULD

USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER.

GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO
FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION.

EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING
EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE

MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF
UNCONSCIOUS.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:420F,216C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:AV

OID SPREADING LIQUID AND FIRE BY WATER
FLOODING. EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. WIPE OR MOP UP OR ABSORB WITH
DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE IN APPROPRIATE
CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE THE MAXIMUM
RECOMMENDED OPER
ATING TEMPERATURE OF 420F. MAY SOFTEN SOME PLASTIC
AND PAINT SURFACES. WIPE UP SPILLS IMMEDIATELY.
Other Precautions:AVOID EYE AND SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED, USE APPROPRIATE NIOSH-APPROVED
RESPIRATORY PROTECTIVE EQUIPMENT.
Ventilation:LOCAL EXHAUST AND MECHANICAL VENTILATION RECOMMENDED.
Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL
Eye Protection:USE CHEMICAL SPLASH GOGGLES
Other P
rotective Equipment:EYE WASH STATION & SAFETY SHOWER. CHEMICALLY
RESISTANT BOOTS AND APRONS RECOMMENDED.
Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH
THOROUGHLY AFTER USE AND BEFORE EATING OR SMOKING.
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>400F,>204C
Vapor Pres:1
Spec Gravity: