

UNI-KEM INTERNATIONAL INC. -- VV-P-236A -- 9150-00-250-0933

===== Product Identification =====

Product ID:VV-P-236A

MSDS Date:06/01/1990

FSC:9150

NIIN:00-250-0933

MSDS Number: BJNVM

=== Responsible Party ===

Company Name:UNI-KEM INTERNATIONAL INC.

Address:513 HICKORY AVE

City:HARAHAN

State:LA

ZIP:70123

Country:US

Info Phone Num:504-738-1623

Emergency Phone Num:504-738-1623

CAGE:4S446

=== Contract

or Identification ===

Company Name:UNI-KEM INTERNATIONAL

Address:1001 HARIMAW COURT EAST

Box:City:METAIRIE

State:LA

ZIP:70001

Country:US

Phone:504-835-7600/FAX:504-835-7608

CAGE:4S446

===== Composition/Information on Ingredients =====

Ingred Name:GREASE, PETROLEUM

CAS:8009-03-8

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:NDA

Explanat

ion of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:NDA

Medical Cond Aggravated by Exposure:NDA

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH IMMEDIATELY WITH COLD WATER, CALL A PHYSICIAN.
SKIN CONTACT:FOR MOLTEN PETROLATUM, FLUSH IMMEDIATELY WITH COLD WATER, CALL A PHYSICIAN. FOR SOLIDIFIED PETROLATUM REMOVE EXCESS WITH PAPER TO WELS, WASH WITH SOAP AND WATER. INHALATION:NDA.
INGESTION:CALL A PHYSICIAN.

==
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>400F,>204C
Lower Limits:NDA
Upper Limits:NDA
Extinguishing Media:DRY CHEMICAL, CO2, FOAM, WATERFOG OR SAND/EARTH.
Fire Fighting Procedures:WATER SPRAY IS AN UNSUITABLE EXTINGUISHING AGENT. FIRE FIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS TO PROTECT AGAINST SMOKE INHALATION.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====
=

Spill Release Procedures:SHUT OFF LEAK AND DIKE UP LARGE SPILLS, AFTER COOLING AND SOLIDIFICATION, SCRAPE AND/OR SHOVEL UP MATERIAL. FINALLY, CLEAN AREA WITH AN OIL ABSORBENT MATERIAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM FLAME, HEAT (200 DEGREES F MAX) AND STRONG OXIDIZING AGENTS. AVOID SKIN AND EYE CONTACT.
Other Precautions:NONE

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:NDA
Protective Gloves:WEAR IMPERVIOUS GLOVES.
Eye Protection:WEAR A FACE SHIELD OVER SAFETY GOGGLES
Other Protective Equipment:WEAR OVERALLS
Work Hygienic Practices:READ ALL LABELS CAREFULLY BEFORE USING.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:NDA
Melt/Freeze Pt:M.P/F.P Text:109F,43C
Vapor Pres:ND
A
Vapor Density:NDA
Spec Gravity:NDA
Evaporation Rate & Reference:NDA
Solubility in Water:NIL
Appearance and Odor:SEMI-SOLID, OIL LIKE, OPAQUE COLOR: YELLOW OR BROWN.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE , AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informat

ion to their
particular situation.