View NSN Online: https://aerobasegroup.com/nsn/6850-00-703-7406

MAGNAFLUX CORPORATION -- ZA-43 KIT, ZL-27A ZYGLO PENETRANT(POST 1/89

6850-00-703-7406

Product ID:ZA-43 KIT, ZL-27A ZYGLO PENETRANT(POST 1/89

MSDS Date:01/06/1989

FSC:6850

NIIN:00-703-7406

MSDS Number: BJNWY === Responsible Party ===

Company Name: MAGNAFLUX CORPORATION

Address:7300 W LAWRENCE AVE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:70

8-867-8000

Emergency Phone Num:708-867-8000 Preparer's Name:BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name: WHITE MINERAL OIL

CAS:8042-47-5

RTECS #:PY8047000 Fraction by Wt: @30%

Other REC Limits: NONE SPECIFIED

Ingred Name: ALIPHATIC PETROLEUM

SOLVENT CAS:8008-20-6 RTECS #:OA5500000 Fraction by Wt: @10% Other REC Limits: NONE SPECIFIED Ingred Name: ISOBUTANE CAS:75-28-5 RTECS #:TZ4300000 Fraction by Wt: 30% Other REC Limits: NONE SPECIFIED ============ Hazards Identification ========================= Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: SEE SIGNS AND SYMPTOMS Effects of Overexposure: INHALATION: DIZZINESS, NAUSEA. SKIN: IRRITAT ION. DISSOLVES SKIN OILS. EYE: MILDLY IRRITATING INGESTION: GASTRIC UPSET. Medical Cond Aggravated by Exposure: NONE First Aid:INHALATION:REMOVE TO FRESH AIR. SKIN:USE SOOTHING LOTION. EYE:RINSE COPIOUSLY WITH WATER, INGESTION:CALL PHYSICIAN IF SEVERE. ============ Fire Fighting Measures ========================= Flash Point Method:PMCC Flash Point: 100F, 38C Lower Limits:1 **Upper Limits:6** Extinguishing Media: CARBO N DIOXIDE, FOAM Fire Fighting Procedures: KEEP CONTAINERS COOL WITH WATER SPRAY. \*DO NOT SPRAY WATER ON BURNING ZL-27A. Unusual Fire/Explosion Hazard: AEROSOL CANS MAY BURST AT TEMPERATURES OVER 130F AND SPRAY OUT FLAMMABLE LIQUID. ======== Accidental Release Measures ============= Spill Release Procedures: NONE SPECIFIED BY MANUFACTURER. =========== Handling and Storage ============================

Handling and Storage Precautions: NONE SPECIFIED BY MANUFACTURER.

Other Precautions: NONE SPECIFIED BY MANUFACTURER. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: RESPIRATOR WITH CHEMICAL CARTRIDGE IF USING IN POORLY VENTILATED AREA. Ventilation: USE IN SPRAY BOOTH OR WHERE VENTILATION IS ADEQUATE TO CARRY VAPORS AND OVERSPRAY FROM OCCUPIED AREAS. Protective Gloves: NITRILE RUBBER GLOVES. Eye Protection: FULL GOGGLES WHEN SPRAYING OR POURING. Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygi enic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health ITEM IS 4 PARTS KIT WHICH ARE AS FOLLOWS: PENETRANT, ZL-27A (REPLACES ZL-22D) - 1 CAN; DEVELOPER, ZP-9E - 1 CAN; DEVELOPER, ZP-4B - 2 CANS; CLEANER/REMOVER, SKC-NF/ZC-7C - 4 CANS. THIS ENTRY DESCRIBES CLEANER/REMOVER; KEY1:F1 ======== Physical/Chemical Properties =========== Boiling Pt:B.P. Text:44.0F,6.7C

HCC:V3 Vapor Pres:105 PSI Vapor Density: