

INDEPENDENT ENERGY CO DIV OF INDEPENDENT CORP. -- WATER WHITE KEROSENE --
9140-00-242-6751

=====
Product Identification
=====

Product ID:WATER WHITE KEROSENE

MSDS Date:04/04/1989

FSC:9140

NIIN:00-242-6751

MSDS Number: BJPDB

=== Responsible Party ===

Company Name:INDEPENDENT ENERGY CO DIV OF INDEPENDENT CORP.

Box:957

City:ELYRIA

State:OH

ZIP:44036

Country:US

Info Phone Num:216-327-7100

Emergency P

hone Num:800-366-5303

CAGE:7U271

=== Contractor Identification ===

Company Name:INDEPENDENT ENERGY CO DIV OF INDEPENDENT CORP.

Box:957

City:ELYRIA

State:OH

ZIP:44036

Country:US

Phone:800-366-5303

CAGE:7U271

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM(T); 400 PPM

ACGIH TLV:400 PPM

=====
Hazards Identification
=====

=====
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRITATION TO EYES, NOSE,
THROAT, SKIN AND LOSS OF COORDINATION. CHRONIC: MAY PRODUCE SKIN
TUMORS WITH PROLONGED AND EXCESSIVE CONTACT. WILL CAUSE SKIN DRYING
AND CRACKING.

Explanation of Carcinogenicity:LIMITED ANIMAL EVIDENCE INDICATES
PRODUCT MAY BE A CARCINOGENIC RISK CHEMICAL TO MAN.

Effects of Overexposure:OVEREXPOSURE MAY LEAD TO EYE, NOSE, THROAT, AND
SKIN IRRITATION. MAY CAUSE LOSS OF COORDINATION.

Medical Conditions Aggravated by Exposure:PERSONS WITH A SKIN DISORDERS SUCH
AS DERMATITIS SHOULD USE CAUTION WHEN HANDLING OR USING THIS
PRODUCT.

=====
First Aid Measures

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH
RESUSCITATION IF NOT BREATHING. GIVE OXYGEN IF BREATHING IS
DIFFICULT. GET MEDICAL ATTENTION. EYES: FLUSH WITH RUNNING WATER
FOR 15 MINUTES WHILE HOLDING EYELID. GET MEDICAL ATTENTION. SKIN:
WASH WITH PLENTY OF SOAP & WATER. REMOVE CONTAMINATED CLOTHING. GET
MEDICAL ADVICE. INGESTED: DO NOT INDUCE VOMITING. GET MEDICAL
ATTENTION IMMEDIATELY.

=====
Fire Fighting Measures

Flash Point Method:CC
Flash Point:100F,38C
Autoignition Temp:Autoignition Temp Text:410F
Lower Limits:0.6
Upper Limits:7.4
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FLAMES, BUT SHOULD
BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. WEAR SCBA WHEN FIRE
FIGHTING IN CONFINED SPACE.

Unusual Fire/Explosion Hazard:HIGHLY VOLATILE, VAPORS MAY BE IGNITED BY
OTHER IGNITION SOURCES.

=====
Accidental Release Measures

Spill Release Procedures:MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE,
OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINER

CONTAINERS. MAJOR:

DIKE & CONTAIN SPILL. ELIMINATE SOURCES OF IGNITION. SHUT OFF
LEAKS. REMOVE LIQUID BY VACUUM OR ABSORBENT. USE FOAM TO CONTROL
VAPORS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL, VENTILATED WORK AREA.
KEEP CONTAINERS CLOSED WHEN NOT IN USE. COMBUSTIBLE LIQUID; EMPTY
CONTAINERS CAN CONTAIN HAZARDOUS RESIDUES.

Other Precautions:NONE

=====
Exposure Controls/Personal Protection
n
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR
FOR HIGH VAPOR CONCENTRATIONS.

Ventilation:USE IN WELL VENTILATED AREA. USE MECHANICAL VENTILATION IN
CONFINED SPACES. KEEP AIR CONCENTRATIONS BELOW TLV.

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SPLASH SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER. WEAR BODY
COVERING WORK CLOTHES TO AVOID PROLONGED OR REPEATED EXPOSURE.

Work

Hygienic Practices:AVOID SKIN CONTACT. WASH THOROUGHLY AFTER USE.
DO NOT EAT OR SMOKE IN WORK AREA. LAUNDRY SOILED CLOTHING BEFORE
REUSE.

Supplemental Safety and Health
NONE

=====
Physical/Chemical Properties
=====

HCC:F4

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:1.0

Vapor Density:>4

Spec Gravity:0.85

Evaporation Rate & Reference:N/K (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, COLORLESS LIQUID. CHARACTERISTIC KEROSE

NE

ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, HALOGENS, STRONG ACIDS, AND STRONG ALKALI.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE AND ASPHYXIANTS.

===== Disposal Considerations =====

Waste Disposal Methods:USER MUST DETERMINE IF THE MATERIAL IS A

HAZARDOUS WASTE. WASTE MAY BE BURNED IN AN APPROVED INCINERATOR OR
DISPOSED OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND
FEDERAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person u

tilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.