

HERCULITE PRODUCTS INC -- CVV ADHESIVE -- 8040-00-159-4885

=====
Product Identification
=====

Product ID:CVV ADHESIVE
MSDS Date:06/03/1985
FSC:8040
NIIN:00-159-4885
MSDS Number: BJPXR
=== Responsible Party ===
Company Name:HERCULITE PRODUCTS INC
Box:786
City:YORK
State:PA
ZIP:17405
Country:US
Info Phone Num:717-764-1191
Emergency Phone Num:717-764-1191
Preparer's Name:LARRY D. RINEHERT
CAGE:4F403

=== Contractor Identification ===
Company Name:HERCULITE PRODUCTS, INC.
Address:ABERDEEN RD
Box:City:EMIGSVILLE
State:PA
ZIP:17318
Country:US
CAGE:4F403

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS

#:AL3150000
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TETRAHYDROFURAN (SARA III)
CAS:109-99-9
RTECS #:LU5950000
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/250 STEL
ACGIH TLV:200 PPM/250STEL;9192
EPA Rpt Qty:1000 L
BS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INHALATION: DIZZINESS, INTOXICATION
WILL RESULT FROM OVEREXPOSURE OF SOLVENT FUMES. INGESTION: SEVERE
GASTRIC IRRITATION WILL RESULT. EYES: EYE CONTACT WITH WET MATERIAL
WILL CAUSE IRRITATION. SKIN: SOLVENTS WILL CAUSE DRYING AND
EVENTUAL CRACKING OF SKIN BY REMOVAL OF ESSENTIAL OILS.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE AFFECTED INDIVIDUAL TO FRESH AIR. CALL
PHYSICIAN IF DIZZINESS PERSISTS. INGESTION: CALL PHYSICIAN OR
EMERGENCY PARAMEDICS. EYES: FLUSH WITH WATER AT LEAST 15 MINUTES.
CALL PHYSICIAN . SKIN: USE A & D OINTMENT OR EQUIVALENT FOR THIS
KIND OF IRRITATION.

=====
===== Fire Fighting Measures =====

Flash Point:39.0F,3.9C
Extinguishing Media:USE CO2 TYPE EXTINGUISHER.
Unu

sual Fire/Explosion Hazard:SOLVENT FUMES ARE FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR APPROVED ORGANIC-VAPOR TYPE RESPIRATOR.
USE ABSORBENT MATERIAL, SCOOP INTO DRUM AND REMOVE TO OPEN AIR FOR
SOLVENT EVAPORATION. DRIED RESIDUE IS NOT HAZARDOUS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID FLAMES AND SPARKS IN USE AREA.
Other Precautions:MATERIAL WILL ATTACK AND SOFTEN CERTAIN PLASTICS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED ORGANIC-VAPOR TYPE RESPIRATORS SHOULD
BE USED IF VENTILATION IS INADEQUATE.
Ventilation:FANS, EXHAUST HOODS, ETC. SHOULD BE USED TO KEEP VAPOR
CONCENTRATION AS LOW AS POSSIBLE.
Protective Gloves:GOGGLES, IF NECESSARY.
Eye Protection:GLOVES, IF NECESSARY.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

H
CC:F2
Spec Gravity:0.9
Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

STRONG OXIDIZERS.
Stability Condition to Avoid:AVOID HEAT.
Hazardous Decomposition Products:UNDER FIRE CONDITIONS MATERIAL WILL
RELEASE HYDROGEN CHLORIDE GAS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compi

ling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.