

FIBER-RESIN CORPORATION -- FR-7035 FILM ADHESIVE -- 8040-00-180-6149

===== Product Identification =====

Product ID:FR-7035 FILM ADHESIVE

MSDS Date:07/10/1990

FSC:8040

NIIN:00-180-6149

MSDS Number: BJPXV

=== Responsible Party ===

Company Name:FIBER-RESIN CORPORATION

Address:170 W. PROVIDENCIA AVE

City:BURBANK

State:CA

ZIP:91502

Country:US

Info Phone Num:800-424-9300

Emergency Phone Num:800-424-9300

0

Preparer's Name:SAM ENGEL, SR.

CAGE:DO271

=== Contractor Identification ===

Company Name:3H B FULLER CO

Box:City:BURBANK

State:CA

ZIP:91503

Country:US

Phone:800-624-9487;612-481-3300

CAGE:0HB93

Company Name:FIBER-RESIN CORP.

Address:170 W PROVIDENCIA AVE

Box:91503

City:BURBANK

Phone:800-424-9300

CAGE:DO271

===== Composition/Information on Ingredients =====

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER RESIN

CAS:25068-38-6

RTECS #:KD4380000

Fraction by Wt: 10-20%

Other REC Limits

:NONE SPECIFIED

Ingred Name:BISPHENOL A DIGLYCIDYL ETHER RESIN

CAS:25036-25-3

Fraction by Wt: 13-30%

Other REC Limits:NONE SPECIFIED

Ingred Name:ACRYLONITRILE BUTADIENE RESIN

CAS:68891-50-9

Fraction by Wt: 3-6%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:NONE

Ingred Name:ACRYLONITRILE (SARA III)

CAS:107-13-1

RTECS #:AT5250000

Fraction by Wt: 1-3%

Other REC Limits:NONE SPECIFIED

OSHA PEL:SEE 1910.1045

ACGIH TLV:S, 2 PPM;A2 9394

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:RESORCINOL DIG

LYCIDYL ETHER

CAS:101-90-6

RTECS #:VH1050000

Fraction by Wt: 0.5-1%

Other REC Limits:NONE SPECIFIED

Ingred Name:POLYAMIDE RESIN

CAS:68989-76-4

Fraction by Wt: 0.5-2%

Other REC Limits:NONE SPECIFIED

Ingred Name:MODIFIED TERTIARY AMINE

CAS:51365-20-9

RTECS #:NM1275000

Fraction by Wt: 490F,>254C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MA

Y

BE TOXIC.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER SPILLED MATERIAL AND PLACE IN SUITABLE CONTAINER FOR REUSE OR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT 40 F OR BELOW.

Other Precautions:MATERIAL IS NON-HAZARDOUS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED.

Ventilation:MECHA

NICAL

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH FOUNTAIN-SAFETY SHOWER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Solubility in Water:INSOLUBLE

Appearance and Odor:CREAM COLORED, TACKY FILM, SLIGHT ODOR

Percent Volatiles by Volume:< 1.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES.

Stability Condition to Avoid:MATERIAL WILL REACT SLOWLY IF NOT STORED AT RECOMMENDED TEMPERATURES.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN.

Conditions to Avoid Polymerization:STORE AT 40 F OR BELOW. MATERIAL WILL SLOWLY POLYMERIZE AT HIGHER TEMPERATURES.

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR INCINERATE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Di

sclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.