View NSN Online: https://aerobasegroup.com/nsn/8010-00-526-1609

CHEMRAY COATING CORP. -- ENAM SEMIGLOSS RUST INHIBIT MARINE CORP GRN 8010-00-526-1609

Product ID: ENAM SEMIGLOSS RUST INHIBIT MARINE CORP GRN MSDS Date:08/03/1990 FSC:8010 NIIN:00-526-1609 **MSDS Number: BJQCL** === Responsible Party === Company Name: CHEMRAY COATING CORP. Address:209 N. MICHIGAN AVE. City:KENILWORTH State:NJ ZIP:07033 Country:US Info Phone Num:201 -245-1111 8:30 TO 4:30 Emergency Phone Num:800-924-9300 CHEMTREC 24 HRS. Preparer's Name: FRED ARMSTRONG CAGE:33832 === Contractor Identification === Company Name: CHEMRAY COATING CORP Address:209 N MICHIGAN AVE Box:City:KENILWORTH State:NJ ZIP:07033 Country:US Phone:201-245-1111 CAGE:33832

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 38.6% Other REC Limits:NONE SPECIFIED OSHA PEL:500 PPM ACGIH T LV:100 PPM; 9293

Ingred Name:LEAD CHROMATE (AS PB CRO4) CAS:7758-97-6 RTECS #:GB2975000 Fraction by Wt: 13.27% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3 ACGIH TLV:0.05 MG/M3

Ingred Name:RED LEAD (AS PBO & PB034) CAS:1314-41-6 RTECS #:OG5425000 Fraction by Wt: 5.74% Other REC Limits:NONE SPECIFIED OSHA PEL:005 MG/M3 ACGIH TLV:005 MG/M3

Ingred Name:LEAD DRIER (AS PB) Fraction by Wt: 0.13% Other REC Limits:NONE SPECIFIED OSHA PEL:005 MG/M3 ACGIH TLV:005 MG/M3

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: HIGH VAPOR CONCENTRATIONS (GREATER THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES & THE **RESPIRATORY TRACT, MAY CAUSE HEADACHES & DIZZINESS, ARE ANESTHETIC** & MAY HAVE OTHER CENTRAL NERVOUS SYS TEM EFFECTS. CONTAINS LEAD, MAY CAUSE LEAD POISONING. Explanation of Carcinogenicity:CHROMAT ES ARE LISTED AS CARCINOGENS Effects of Overexposure: HIGH VAPOR CONCENTRATIONS (GREATER THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES & THE **RESPIRATORY TRACT, MAY CAUSE HEADACHES & DIZZINESS, ARE ANESTHETIC** & MAY HAVE OTHER CENTRAL NERVOUS SYS TEM EFFECTS. Medical Cond Aggravated by Exposure: PRE-EXISTING EYE, SKIN & RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EY

ES:FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION SUBSIDES, IF IRRITATION PERSISTS CALL A PHYSICIAN. SKIN:REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WATER. INHALATION:IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL A PHYSICIAN. INGESTION:DO NOT INDUCE VOMITING, CALL A PHYSICIAN.

Flash Point Method:SCC Flash Point:103 F/40 C Autoignition Temp: Autoignition Temp Text: 473F Lower Limits:0.9 Upper Limits:7 Extinguishing Media: CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL. Fire Fighting Procedures: USE AIR SUPPLIED BREATHING EQUIPMENT. COOL ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR FUMES. Unusual Fire/Explosion Hazard: IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS. Spill Release Procedures: REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS, O PEN FLAME. ADD ABSORBENT(SAND, EARTH, SAWDUST). VENTILATE AREA(OPEN WINDOWS, DOORS). IF LARGE: KEEP PRODUCT FROM ENTERING SEWERS & WATERCOURSES BY DIK ING. ADVISE AUTHORITIES IF PRODUCT DOESENTER. Handling and Storage Precautions: STORE AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRY, WELL VENTILATED AREA. AVOID DIRECT SUNLIGHT & EXTREME TEMPERATURES-HOT OR COLD. Other Precautions: AVOID EYE, SKIN CONTACT, INHALATI **ON & INGESTION OF** MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST. Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR **RESPIRATOR IN CONFINED AREAS.** Ventilation:LOCAL EXHAUST:FACE VELOCITY 60FPM. SPECIAL:USE ONLY WITH ADEQUATE VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT. Protective Gloves: CHEMICAL RESISTANT Eve Protection: SPLASH GOGGLES OR FACE SHIELD

Other Protective Eq

uipment:USE CHEMICAL RESISTANT APRON OR CLOTHING. Supplemental Safety and Health

Boiling Pt:B.P. Text:308F,153C Melt/Freeze Pt:M.P/F.P Text:0F,-18C Decomp Temp:Decomp Text:600F,316C Vapor Pres: