View NSN Online: https://aerobasegroup.com/nsn/6140-00-557-3873

CONCORDE BATTERY CORP -- M83769/5-1 BATTERY -- 6140-00-557-3873

============ Product Identification ==============

Product ID:M83769/5-1 BATTERY

MSDS Date:01/01/1987

FSC:6140

NIIN:00-557-3873

MSDS Number: BJQDB === Responsible Party ===

Company Name: CONCORDE BATTERY CORP

Address: 2009 SAN BERNARDINO RD

City:WEST COVINA

State:CA

ZIP:91790-1006 Country:US

Info Phone Num:714-989-8522

Emergency Phone Num:818-962-4006

CAGE:63017

=== Contractor Identification ===

Company Name: CONCORDE BATTERY CORP

Address: 2009 SAN BERNARDINO RD

Box:City:WEST COVINA

State:CA

ZIP:91790-1006 Country:US

Phone:800-255-3924/818-813-1234

CAGE:63017

======= Composition/Information on Ingredients ========

Ingred Name: DRY LEAD OXIDE PASTE

CAS:1317-36-8

RTECS #: OG1750000

Other REC Limits: NONE SPECIFIED

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3;1910.10

25 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB ========== Hazards Identification =============== Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: THE PRODUCT ITSELF IS NONTOXIC. Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure:THE PRO DUCT ITSELF IS NONTOXIC. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid:NONE SPECIFIED BY MANUFACTURER. Flash Point: NONFLAMMABLE Extinguishing Media: USE CARBON DIOXIDE OR DRY CHEMICAL. Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosi on Hazard:TOXIC FUMES PRODUCED BY THE REACTION OF OXIDIZING AGENTS AND LEAD OXIDE. ======== Accidental Release Measures ============

Spill Release Procedures:THE PRODUCT IS A DRY BATTERY & IS CONSIDERED AS NONSPILLABLE, IT IS TO BE PACKAGED ACCORDING TO 49 CFR PARA 178.205 SPECIFICATION 12B. IN CASE OF AN ACCIDENT AND THE CONTAINER IS BROKEN, PROTECTIVE GL OVES ARE REQUIRED TO HANDLE THE BATTERYPARTS.

Neutralizing Agent: SODIUM BICARBONATE

===== Handling and Storage ================
Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER. Other Precautions:NONE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE NORMALLY REQUIRED. Ventilation:NONE NORMALLY REQUIRED. Protective Gloves:NONE NORMALLY REQUIRED. Eye Protection:NONE NORMALLY REQUIRED. Other Protective Equipment:NONE NORMALLY REQUIRED. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATI
Supplemental Safety and Health NONE
========== Physical/Chemical Properties ==========
HCC:N1 Appearance and Odor:ALUMINUM CASED 24 VOLT DRY STORAGE BATTERY, 10.5X11.8X10.2 INCHES
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.
======================================
Waste Disposal Methods:DISPOSE OF BATTERIES IN ACCORDANCE WITH FEDERA

Waste Disposal Methods:DISPOSE OF BATTERIES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS FOR LEAD ACID BATTERIES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any

person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.