

LOCTITE CORPORATION -- WATER PROOFING SOLUTION, SPLICING KIT ORING

=====
MSDS Safety Information
=====

FSC: 4940
NIIN: 01-131-1915
MSDS Date: 01/22/1991
MSDS Num: BJQJF
Product ID: WATER PROOFING SOLUTION, SPLICING KIT ORING
MFN: 02
Kit Part: Y
Responsible Party
Cage: 05972
Name: LOCTITE CORPORATION
Address: 1001 TROUT
BROOK CROSSING
City: ROCKY HILL (FORMALLY IN NEWINGTON) CT 06067
Info Phone Number: 860-571-5100/FAX 860-571-5465
Emergency Phone Number: 860-571-5100/FAX 860-571-5465
Preparer's Name: STEPHEN REPETTO
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 05972
Name: LOCTITE CORPORATION
Address: 1001 TROUT BROOK CROSSING
City: ROCKY HILL CT 06067-3910
Phone: 860-571-5100
Cage: 97403
Name
: US ARMY
Address: RESEARCH AND DEVELOPMENT CENTER
City: FORT BELVOIR VA 22060-5606
Phone: UNKNOWN

=====
Item Description Information
=====

Item Manager: S9C
Item Name: SPLICING KIT O RING
Specification Number: NONE
Type/Grade/Class: NONE
Unit of Issue: KT
UI Container Qty: 1
Type of Container: UNKNOWN

=====
Ingredients
=====

=====
Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (SARA III)
% Wt: 40-45 %
Other REC Limits: NONE SPECIFIED
OSHA PEL: 200 PPM/150 STEL
ACGIH TLV: 50 PPM; 9293
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 78-93-3
RTECS #: EL6475000
Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
% Wt: 25-30 %
Other REC Limits: NONE SPECIFIED
OSHA PEL: 200 PPM/300 STEL
ACGIH TLV: 200 PPM/300STEL 9192
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 64742-48-9
Name: HYDROTREATED HEAVY NAPHTHA
% Wt: 5-10%
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 64742-89-8
Name: NAPHTHA, LIGHT ALIPHATIC
% Wt: 5-10 %
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 9010-98-4
Name: NEOPRENE
% Wt: 5-10 %
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV:

NOT ESTABLISHED

Cas: 22708-90-3

Name: CLAY ALUMINUM SALT

% Wt: 3-5 %

Other REC Limits: NONE SPECIFIED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 1333-86-4

RTECS #: FF5800000

Name: CARBON BLACK

% Wt: 3-5 %

Other REC Limits: NONE SPECIFIED

OSHA PEL: 3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

Name: PHENOLIC RESIN

% Wt: 3-5 %

Other REC Limits: NONE SPECIFIED

OSHA PEL: UNKNOWN

ACGIH TLV: UNKNOWN

--

Cas: 1330-20-7

RTECS #: ZE2100000

Name: XYLENES (O-,M-,P- ISOMERS) (SARA III)

% Wt: 1-3 %

Other REC Limits: NONE SPECIFIED

OSHA PEL: 100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

=====
Health Hazards Data

=====
LD50 LC50 Mixture: > 2000 MG/KG ESTIMATED DERMAL LD50

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingesti

on: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYE IRRITANT. MODERATELY TOXIC BY INGESTION.

Explanation Of Carcinogenicity: PRODUCT CONTAINS NO MATERIALS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Signs And Symptoms Of Overexposure: NAUSEA, HEADACHE, LOSS OF COORDINATION.

Medical Cond Aggravated By Exposure: EYE, LIVER, SKIN, RESPIRATORY AND CENTRAL NERVOUS SYSTEM DISEASES, ALCOHOLISM MAY BE AGGRAVATED BY EXPOSURE.

First Aid: INGESTION: INDUCE

VOMITING. KEEP INDIVIDUAL CALM. OBTAIN MEDICAL

ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, OBTAIN

MEDICAL ATTENTION. SKIN CONTACT: FLUSH WITH WATER. EYE CONTACT: FLUSH AT LEAST 15 MINUTES WITH WATER. OBTAIN MEDICAL ATTENTION.

=====
Handling and Disposal
=====

Spill Release Procedures: SOAK UP WITH AN INERT ABSORBENT. STORE IN A CLOSED CONTAINER AWAY FROM SOURCES OF IGNITION UNTIL DISPOSAL.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: INCINERATE FOLLOWING EPA AND LOCAL REGULATIONS.

Handling And Storage Precautions: STORE BELOW 100F. KEEP AWAY FROM EYES. AVOID PROLONGED BREATHING OF VAPOR. AVOID PROLONGED SKIN CONTACT. AVOID SOURCES OF IGNITION.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.
=====

Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: 30.0F,-1.1C

Lower Limits: 0.9%

Upper Limits: 6 %

Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL

Fire Fighting Procedures: IRRITATING ORGANIC VAPORS FORMED DURING THERMAL DECOMPOSITION. FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRE.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER.
=====

Control Measures
=====

=====
Respiratory Protection: NONE SPECIFIED BY MANUFACTURER.
Ventilation: PROVIDE ADEQUATE LOCAL VENTILATION TO MAINTAIN VAPOR CONCENTRATION BELOW TLV.
Protective Gloves: RUBBER OR PLASTIC GLOVES.
Eye Protection: SAFETY GLASSES OR GOGGLES
Other Protective Equipment: EYEWASH STATION, SAFETY SHOWER.
Work Hygienic Practices: AVOIDED PROLONGED SKIN CONTACT.
Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER.
=====

=====
Physical/Chemical Properties
=====

HCC: F2
B.P. Text: 190F,88C
M.P/F.P Text: UNKNOWN
Decomp Text: UNKNOWN
Vapor Pres: UNKNOWN
Vapor Density: UNKNOWN
Spec Gravity: 0.85 @80F
Viscosity: UNKNOWN
Evaporation Rate & Reference: UNKNOWN
Solubility in Water: SLIGHT
Appearance and Odor: BLACK LIQUID, SWEET ODOR
Corrosion Rate: UNKNOWN
=====

Reactivity Data
=====

=====
Stability Indicator: YES
Stability Condition To Avoid: HIGH TEMPERATURES
Materials To Avoid: NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products: IRRITATING ORGANIC VAPORS
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NONE. WILL NOT OCCUR.
=====

Toxicological Information
=====

=====
Ecolo

gical Information

MSDS Transport Information

Regulatory Information

Other Information

Transportation Information

Responsible Party Cage: 05972

Trans ID NO: 109651

Product ID: WATER PROOFING SOLUTION, SPLICING KIT ORING

MSDS Prepared Date: 01/22/1991

Review Date: 03/18/1991

MFN: 2

Tech Entry NOS Shipping Nm: TOLUENE 40-45 %

Net Unit Weight: 1 OUNCE

Multiple KIT Number: 0

Kit Part IND: Y

Review IND: Y

Unit Of Issue: KT

Container QTY: 1

Type Of Container: UNKNOWN

Additional Data: THIS IS P

ART B OF A KIT. THIS COMPONENT GOVERNS THE SHIPPING

LABEL. ABOVE CODES APPLY IF AMOUNT SHIP PED IS LESS THAN 1 PINT. IF MORE THAN
1 PINT SHIPPED: NAX;OSR;YEL;JKT, TOLUENE SOLUTION.

Detail DOT Information

DOT PSN Code: DTJ

Symbols: D

DOT Proper Shipping Name: CONSUMER COMMODITY

Hazard Class: ORM-D

Label: NONE

Non Bulk Pack: 156,306

Bulk Pack: NONE

Max Qty Pass: 30KGGROSS

Max Qty Ca

rgo: 30KGGROSS
Vessel Stow Req: A

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
=====

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
HAZCOM Label
=====

Product ID: WATER PROOFING SOLUTION, SPLICING KIT ORING
Cage: 05972
Company Name: LOCTITE CORPORATION
Street: 1001 TROUT BROOK CROSSING
City: ROCKY HILL CT
Zipco
de: 06067-3910
Health Emergency Phone: 203-278-1280
Label Required IND: Y
Date Of Label Review: 03/18/1991
Status Code: C
MFG Label NO: NONE
Label Date: 03/18/1991
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: Severe
Reactivity Hazard: None
Hazard And Precautions: STORE BELOW 100F. KEEP AWAY FROM EYES. AVOID PROLONGED
BREATHING OF VAPOR. AVOID PROLONGED SKIN CONTACT. AVOID SOURCES OF IGNITION.

FIRST AID: INGESTION: INDUCE VOMITING. KEEP INDIVIDUAL CALM. OBTAIN MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, OBTAIN MEDICAL ATTENTION. SKIN CONTACT: FLUSH WITH WATER. EYE CONTACT: FLUSH AT LEAST 15 MINUTES WITH WATER. OBTAIN MEDICAL ATTENTION.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.