View NSN Online: https://aerobasegroup.com/nsn/8010-00-160-5851

BAKER SEALANTS & COATINGS COMPANY -- TT-V-121H WATER RESISTING SPAR VARNISH -- 8010-00-160-5851

Product ID:TT-V-121H WATER RESISTING SPAR VARNISH MSDS Date:04/19/1989 FSC:8010 NIIN:00-160-5851 MSDS Number: BJQMT === Responsible Party === **Company Name: BAKER SEALANTS & COATINGS COMPANY** Address:234 SUYDAM AVENUE Box:B City: JERSEY CITY State:NJ ZIP:07304 Country:US Info Phone Num:201-333-6986 Emergency Phone Num:201-333-6986 CAGE:FO833 === Contractor Identification === Company Name: BAKER SEALANTS & COATINGS CO., INC. Address:234 SUYDAM AVENUE Box:B City: JERSEY CITY State:NJ ZIP:07304-3306 Phone: (201) 333-6986 CAGE:FO833 Company Name: BAKER SEALANTS AND COATINGS CO Address:234 SUYDAM AVE Box:City:JERSEY CITY State:NJ ZIP:07304-3306 Country:US Phone:201-333-6986 CAGE:34094 Company Name: STEVEN INDUSTRIES Address:39 AVENUE C Box:8 **City:BAYONNE** State:NJ ZIP:0700

Phone:201-437-6501 CAGE:33150 Ingred Name: MINERAL SPIRITS, EXEMPT Fraction by Wt: 45% **OSHA PEL:500 PPM** ACGIH TLV:125 PPM Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic: EYES: HIGH VAPOR CONC MAY BE IRRIT. SKIN: SLIGHTLY IRRIT. PROLONGED/REPEATED EXPOSURE-DEFATTING, DRY SKIN, LEADING TO IRR IT/DERMATITIS. INHALE: HIGH VAPOR CONC IRRIT TO NOSE, RESPIRATORY TRACT. MAY CA USE CENTRAL NERVOUS SYSTEM DEPRESSION. UNCONSCIOUSNESS/DEATH MAY OCCUR. INGEST: AVOID ASPIRATION OF VOMITUS INTO LUNGS. Effects of Overexposure: INHALATION: GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA. INGESTION: MAY RESULT IN VOMITING OR ASPIRATION PNEUMONITIS WHICH MAY BE EVIDENCED BY COUGHING, LABORED BREATHING AND CYANOSIS (BLUISH SKIN). IN SEVERE CASES, DEATH MAY OCCUR. Medical Cond Aggrava ted by Exposure: PRE-EXISTING EYE, SKIN, AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. First Aid: EYES: FLUSH W/WATER-15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN: FLUSH W/WATER. REMOVE CONTAM CLOTH & SHOES. WASH W/SOAP & WATER. DO NOT REUSE CLOTH OR SHOES UNTIL CLEAN. INHALE: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING DIFFICULT. GIVE CPR IF NOT **BREATHING. INGESTION: DO NO** T INDUCE VOMIT. IF VOMIT OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS. GET NEEDED MED ATTN. Flash Point Method:TCC Flash Point:105F,41C Lower Limits:1 Upper Limits:6 Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM OR DRY CHEMICAL. Fire Fighting Procedures: DON'T ENTER CONFINED FIRE SPACE W/O FULL GEAR & SCBA.COOL FIRE EXPOSED CNTNRS W/WATER.DON'T USE DIRECT STREAM WATER ON

2-3417 Country:US POOL FIRE,WILL FLOAT/REIGNITE ON SURFACE. Unusual Fire/Explosion Hazard:COOL CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES W/WATER TO PREVENT VAPOR PRESS BUILDUP,MAY RUPTURE. COOL AREA W/LG AMTS WATER/PREVENT WEAKENING OF CONTAINER.

Spill Release Procedures:CAUTION!COMBUSTIBLE!ELIMINATE IGNITE SOURCE.WEAR RSPRTR/PROTECT CLOTH.IF SAFE TO DO,SHUT OFF LEAK SOURCE,DIKE,CONTAIN.REMOVE W/VACUUM TRUCKS/PUMP TO STORAGE /SALVAGE

VESS.SOAK UP W/ABSORB/PUT IN NON-LE AK CNTNRS/SEAL TIGHT.FLUSH AREA W/WATER/DISPOSE.

Handling and Storage Precautions: KEEP LIQUID/VAPOR FROM IGNITE SOURCE. MAY IGNITE W/O SPARK/FLAME. VAPOR MAY ACCUMULATE, TRAVEL TO IGNITE SOURCE DISTANT FROM HANDLING SITE/FLASH-FIRE.

Other Precautions: KEEP CLOSED WHEN NOT IN USE. USE W/ADEQUATE VENT. CONTAINERS, EVEN EMPTY, CONTAIN EXPLOS VAPORS. DO NOT CUT, DRILL

GRIND, WELD, ETC. ON/NEAR CONTAINERS. STATIC ELEC MAY ACCUM & CREATE FIRE HAZARD. GR OUND FIXED EQUIP & TRANSFER CONTAINERS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS, USE NIOSH-APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVEREXPOSURE. PER 29 CFR 1910, 134, USE EITHER ATMOSPHERE-SUPPLYING RESPIRATOR OR AIR- PURIFYING RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:US

E EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS WITHIN SUGGESTED PEL/TLV LIMITATIONS. Protective Gloves: CHEMICAL-RESISTANT GLOVES.

Eye Protection: SAFETY GLASSES OR GOGGLES AS APPROPRIATE

Other Protective Equipment:SAFETY SHOWER, EYE BATH, AND WASHING FACILITIES SHOULD BE AVAILABLE. USE OTHER CLOTHING AS REQUIRED TO MINIMIZE COST.

Work Hygienic Practices: WASH W/SOAP & WATER BEFORE EATING, DRINKING, SMOKING, USING TOILET FACILITIES. NO SMOKING WHERE MATERI

AL IS

USED/STORED.

Supplemental Safety and Health

IF MORE THAN 2.0 ML PER KG INGESTED & VOMIT HAS NOT OCCURRED, INDUCE EMESIS W/SUPERVISION. IF LOSS OF GAG REFLEX, CONVULSIONS, UNCONSCIOUSNESS OCCUR BEFORE EMESIS, CONSIDER GASTRIC LAVAGE USING CUFFED ENDOTRACHEAL TUBE. REPORT SPILLS INTO/LEADING TO WATER SURFACE CAUSING "SHEEN" TO NAT'L RESPONSE CENTER. STORE/COOL.

Boiling Pt:B.P. Text:323 TO 390F Vapor P res:0.1 PSI Vapor Density:> AIR Spec Gravity:.881 Evaporation Rate & amp; Reference:SLOWER THAN ETHER

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM OR CALCIUM HYPOCHLORITE.
Stability Condition to Avoid:AVOID HEAT AND FLAME.
Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS DURING COMBUSTION.

Waste Disposal Methods:SEAL CONTAINERS, LABEL PROPERLY & DISPATCH TO APPROVED WASTE DISPOSAL FACILITY. ASSURE COMPLIANCE W/LOCAL, STATE & FED REGS. IF BECOMES WASTE MATERIAL, WOULD BE IGNITABLE HAZARDOUS WASTE, #D001. REFER TO LATEST EPA OR STATE REGS FOR PROPERDISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.