View NSN Online: https://aerobasegroup.com/nsn/8010-00-160-5852

BAKER SEALANTS & COATINGS COMPANY -- TT-V-121H, WATER RESISTING SPAR VARNISH -- 8010-00-160-5852

Product ID:TT-V-121H, WATER RESISTING SPAR VARNISH

MSDS Date:04/19/1989

FSC:8010

NIIN:00-160-5852

MSDS Number: BJQMV === Responsible Party ===

Company Name: BAKER SEALANTS & COATINGS COMPANY

Address:234 SUYDAM AVENUE

Box:B

City: JERSEY CITY

State:NJ ZIP:07304 Country:U

S

Info Phone Num:201-333-6986

Emergency Phone Num:201-333-6986

CAGE:FO833

=== Contractor Identification ===

Company Name: BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone: (201) 333-6986

CAGE:FO833

Company Name: BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name: STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ ZIP:07 002-3417 Country:US Phone:201-437-6501

CAGE:33150

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS, EXEMPT

Fraction by Wt: 45% OSHA PEL:500 PPM **ACGIH TLV:125 PPM** 

=========== Hazards Identification ==========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EYES: HIGH VAPOR CONC MAY BE IRRIT.

SKIN: SLIGHTLY IRRIT. PROLONGED/REPEATED EXPOSURE-DEFATTING, DRY

SKIN, LEADING TO I

RRIT/DERMATITIS. INHALE: HIGH VAPOR CONC IRRIT TO

NOSE, RESPIRATORY TRACT. MAY CA USE CENTRAL NERVOUS SYSTEM DEPRESSION. UNCONSCIOUSNESS/DEATH MAY OCCUR. INGEST: AVOID ASPIRATION OF VOMITUS INTO LUNGS.

Effects of Overexposure: INHALATION: GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA. INGESTION: MAY RESULT IN VOMITING OR ASPIRATION PNEUMONITIS WHICH MAY BE EVIDENCED BY COUGHING, LABORED BREATHING AND CYANOSIS (BLUISH SKIN). IN SEVERE CASES, DEATH MAY OCCUR.

Medical Cond Aggra

vated by Exposure:PRE-EXISTING EYE, SKIN, AND

RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EYES: FLUSH W/WATER-15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN: FLUSH W/WATER. REMOVE CONTAM CLOTH & SHOES. WASH W/SOAP & WATER. DO NOT REUSE CLOTH OR SHOES UNTIL CLEAN. INHALE: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING DIFFICULT. GIVE CPR IF NOT BREATHING. INGESTION: DO

NOT INDUCE VOMIT. IF VOMIT OCCURS.KEEP

HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS. GET NEEDED MED ATTN.

Flash Point Method:TCC Flash Point: 105F,41C

Lower Limits:1 **Upper Limits:6** 

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM OR DRY CHEMICAL.

Fire Fighting Procedures: DO NOT ENTER CONFINED SPACE W/O FULL GEAR & SCBA. COOL FIRE EXPOSED CNTNRS W/WATER. DO NOT USE DIRECT STREAM WATER ON

POOL FIRES, WILL FLOAT/REIGNITE ON SURFACE
Unusual Fire/Explosion Hazard: COOL CONTAINERS EXPOSED TO INTENSE HEAT
FROM FIRES W/WATER TO PREVENT VAPOR PRESS BUILDUP, MAY RUPTURE. COOL
AREA W/LG AMTS WATER/PREVENT WEAKENING OF CONTAINER.

========= Accidental Release Measures =============

Spill Release Procedures:CAUTION!COMBUSTIBLE!ELIMINATE IGNITE SOURCE.WEAR RSPRTR/PROTECT CLOTH.IF SAFE TO DO,SHUT OFF LEAK SOURCE,DIKE,CONTAIN.REMOVE W/VACUUM TRUCKS/PUMP TO STORA GE/SALVAGE

VESS.SOAK UP W/ABSORB/PUT IN NON-LE AK CNTNRS/SEAL TIGHT.FLUSH AREA W/WATER/DISPOSE.

============ Handling and Storage ===============

- Handling and Storage Precautions:KEEP LIQUID/VAPOR FROM IGNITE SOURCE.

  MAY IGNITE W/O SPARK/FLAME. VAPOR MAY ACCUMULATE, TRAVEL TO IGNITE SOURCE DISTANT FROM HANDLING SITE/FLASH-FIRE.
- Other Precautions: KEEP CLOSED WHEN NOT IN USE. USE W/ADEQUATE VENT. CONTAINERS, EVEN EMPTY, CONTAIN EXPLOS VAPORS. DO NOT CUT, DRI LL.
  - GRIND, WELD, ETC. ON/NEAR CONTAINERS. STATIC ELEC MAY ACCUM & CREATE FIRE HAZARD. GR OUND FIXED EQUIP & TRANSFER CONTAINERS.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS, USE NIOSH-APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVEREXPOSURE. PER 29 CFR 1910, 134, USE EITHER ATMOSPHERE-SUPPLYING RESPIRATOR OR AIR- PURIFYING RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:

USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS WITHIN SUGGESTED PEL/TLV LIMITATIONS.

Protective Gloves: CHEMICAL-RESISTANT GLOVES.

Eye Protection: SAFETY GLASSES OR GOGGLES AS APPROPRIATE

- Other Protective Equipment:SAFETY SHOWER, EYE BATH, AND WASHING FACILITIES SHOULD BE AVAILABLE. USE OTHER CLOTHING AS REQUIRED TO MINIMIZE COST.
- Work Hygienic Practices: WASH W/SOAP & WATER BEFORE EATING, DRINKING, SMOKING, USING TOILET FACILITIES. NO SMOKING WHERE MATE

RIAL IS USED/STORED.

Supplemental Safety and Health

IF MORE THAN 2.0 ML PER KG INGESTED & VOMIT HAS NOT OCCURRED, INDUCE EMESIS W/SUPERVISION. IF LOSS OF GAG REFLEX, CONVULSIONS, UNCONSCIOUSNESS OCCUR BEFORE EMESIS, CONSIDER GASTRIC LAVAGE USING CUFFED ENDOTRACHEAL TUBE. REPORT SPILLS INTO/LEADING TO WATER SURFACE CAUSING "SHEEN" TO NAT'L RESPONSE CENTER. STORE/COOL.

======== Physical/Chemical Properties ===========

HCC:F4

Boiling Pt:B.P. Text:323 TO 390

F

Vapor Pres:0.1 PSI Vapor Density:> AIR Spec Gravity:.881

Evaporation Rate & Deference: SLOWER THAN ETHER

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM OR CALCIUM HYPOCHLORITE.

Stability Condition to Avoid: AVOID HEAT AND FLAME.

Hazardous Decomposition Products: CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS DURING COMBUSTION.

=====

====== Disposal Considerations ==========

Waste Disposal Methods:SEAL CONTAINERS, LABEL PROPERLY & DISPATCH TO APPROVED WASTE DISPOSAL FACILITY. ASSURE COMPLIANCE W/LOCAL, STATE & FED REGS. IF BECOMES WASTE MATERIAL, WOULD BE IGNITABLE HAZARDOUS WASTE, #D001. REFER TO LATEST EPA OR STATE REGS FOR PROPERDISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of D

efense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.