

GC ELECTRONICS -- RUBBER TO METAL CEMENT PN 10-352 -- 8040-00-261-8450

=====
Product Identification
=====

Product ID:RUBBER TO METAL CEMENT PN 10-352

MSDS Date:10/07/1986

FSC:8040

NIIN:00-261-8450

MSDS Number: BJQPM

=== Responsible Party ===

Company Name:GC ELECTRONICS

Address:1801 MORGAN ST

City:ROCKFORD

State:IL

ZIP:61105

Country:US

Info Phone Num:815-968-9661

Emergency Phone Num:815-968-9661

P

reparer's Name:V. HAGEMAN

CAGE:72653

=== Contractor Identification ===

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL

ZIP:61105

Country:US

Phone:815-968-9661

CAGE:72653

=====
Composition/Information on Ingredients
=====

Ingred Name:ALPHATIC HYDROCARBONS

Fraction by Wt: 74%

Other REC Limits:TLV PEL 100

Ingred Name:ADHESIVE SOLIDS

Fraction by Wt: 26%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:EYE AND SKIN IRRITATION, LOSS OF COORDINATION,
DROWSINESS, HEADACHE, NAUSEA AND VOMITING.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER. SKIN:WATER WITH SOAP AND WATER.
INHALATION:FRESH AIR, OXYGEN AND ARTIFICIAL RESPIRATION IF
NECESSARY. INGESTION:DO NOT INDUCE VOMITING. CALL PHYSICIAN.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:CC
Flash Point:-7F/-22C
Lower Limits:1.2
Upper Limits:8.0
Extinguishing Media:DRY CHEMICAL, CO2, FOAM
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:MATERIAL IS HIGHLY VOLATILE-VAPORS ARE
HEAVY AND MAY TRAVEL TO IGNITION SOURCE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. ABSORB WITH INERT
MATERIAL STORE IN METAL CONTAINER FOR DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. USE ONLY WITH
ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAMES.
Other Precautions:EMPTY CONTAINERS MAY PRESENT EXPLOSION HAZARD DUE TO
REMAINING SOLVENTS/VAPORS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:CARTRIDGE TYPE RESPIRATOR IF TLV LEVEL EXCEEDED.
Ventilation:MECHANICAL
Protective Gloves:IM

PERVIOUS GLOVES IF NECESSARY
Eye Protection:CHEMICAL GOGGLES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:151F,66C
Vapor Pres:125 MM HG
Vapor Density:3.0
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK OPAQUE LIQUID-STRONG SOLVENT ODOR

===== Stability and Reactivity Data =====

STRONG OXIDIZERS OR ALKALIS

Hazardous Decomposition Products:MAY FORM CARBON MONOXIDE, CO2, TOXIC GASES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.