

LAGUNA CLAY CO -- SODIUM BISULFATE

=====
MSDS Safety Information
=====

FSC: 6810
NIIN: 00-270-9984
MSDS Date: 03/25/1991
MSDS Num: BJQQM
Product ID: SODIUM BISULFATE
MFN: 01
Responsible Party
Cage: 40894
Name: LAGUNA CLAY CO
Address: 14400 LOMITAS AVE
City: LA PUENTE CA 91746
Info Phone N
umber: 818-330-0631
Emergency Phone Number: 818-330-0631
Preparer's Name: DELISA B. DAVIS
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 40894
Name: LAGUNA CLAY CO
Address: 14400 LOMITAS AVE
City: LA PUENTE CA 91746

=====
Contractor Summary
=====

Cage: 40894
Name
: LAGUNA CLAY CO
Address: 14400 LOMITAS AVE
City: LA PUENTE CA 91746
Phone: 818-330-0631

=====
Item Description Information
=====

Item Manager: S9G
Item Name: SODIUM BISULFATE, ANHYDROUS, TECHNICAL
Specification Number: MIL-S-16917
Type/Grade/Class: I TYPE
Unit of Issue: DR
Quantitative Expression: 00000000100LB
UI Container Qty: 1
Type of Container: DRUM
=====

=====

Ingredients

=====

Cas: 7681-38-1
RTECS #: VZ1860000
Name: SODIUM BISULFATE
% Wt: >99
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

=====

Health Hazards Data

=====

LD50 LC50 Mixture: ORAL LD50 (RAT) IS UNKNOWN
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds
- NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: NONE SPECIFIED BY MANUFACTURER.
Explanation Of Carcinogenicity: NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Signs And Symptoms Of Overexposure: NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.
Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.
First Aid: INHALE-REMOVE TO FRESH AIR, GIVE CPR OR OXYGEN IF NEED;EYES/SKIN-FLUSH WITH LARGE AMOUNTS WATER FOR 15 MIN;INGEST-R INSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS O F OVEREXPOSURE.

=====

Handling and Disposal

=====

Spill Release Procedures: WEAR PROTECTIVE EQUIPMENTS. RECOVER MUCH AS POSSIBLE.NEUTRALIZE AREA WITH ALKALINE SOLUTION & WASH/FLUSH WITH LG Q OF WATER.
Neutralizing Agent: ALKALINE SOLUTIONS
Waste Disposal Methods: MANUFACTURER SPECIFIED, CAN BE FLUSHED

TO SEWER AFTER

NEUTRALIZATION I/A/W LOCAL, STATE & FEDERAL REGULATIONS.

Handling And Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED AREA.

PROTECT FROM PHYSICAL DAMAGE. AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions: AVOID SKIN CONTACT. DO NOT STORE IN HUMID LOCATION.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: NONE

Extingu

ishing Media: EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS, USE WATER SPRAY TO COOL NEARBY CONTAINERS.

Unusual Fire/Explosion Hazard: ABOVE 570F, FUMES OF SULFUR DIOXIDE ARE EVOLVED. ELIMINATE BY FORCED DRAFT VENTILATION.

=====
Control Measures
=====

Respiratory Protection: WEAR MASK W/INORGANIC-TYPE CANISTER OR DUST MASK

Ventilation: USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves: RUBBER/PLASTIC

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment: FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONG CONTACT.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: MSDS NOT DATED; SPEC REFERENCE:MIL-S-16917,TYPE I. *****MSDS CREATED FOR LUGANA CLAY. LAGUNA CLAY DOES NOT HAVE A MSDS FOR SODIUM BISULFATE. LAGUNA CLAY IS A DISTRIBUTING COMPANY. M SDS CREATED ON 3-25-91.*****

=====
Physical/Chemical Properties
=====

HCC: N1

Solubility in Water: COMPLETE

Appearance and Odor: OFF-WHITE,BEAD LIKE,GRANULAR,DRY MATERIAL

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: NOT KNOWN

Materials To Avoid: STRONG ALKA

LIS
Hazardous Decomposition Products: THERMAL DECOMPOSITION
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT KNOWN

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: 40894

Tra

ns ID NO: 64601

Product ID: SODIUM BISULFATE

MSDS Prepared Date: 03/25/1991

Review Date: 03/02/1998

MFN: 1

Net Unit Weight: 100 LBS

AF MMAC Code: NR

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: DR

Container QTY: 1

Type Of Container: DRUM

Additional Data: GRANULAR DRY MATERIAL.

=====
Detail DOT Information
=====

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANS

PORTATION

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
=====

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
HAZCOM Label
=====

Product ID: SODIUM BISULFATE
Cage: 40894
Company Name: LAGUNA CLAY CO
Street: 14400 LOMITAS AVE
City: LA PUENTE CA
Zipcode: 91746
Health Emergency Phone: 818-330-0631
Label Required IND
: Y
Date Of Label Review: 03/25/1991
Status Code: C
MFG Label NO: UNK
Label Date: 03/25/1991
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: WARNING
Respiratory Protection IND: YES
Health Hazard: Moderate
Contact Hazard: Slight
Fire Hazard: None
Reactivity Hazard: None
Hazard And Precautions: STORE IN COOL, DRY, WELL VENTILATED AREA. PROTECT FROM
PHYSICAL DAMAGE. AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED
FIRST AID: INHALE-REMOVE TO FRESH AIR

, GIVE CPR OR OXYGEN IF NEED;EYE
S/SKIN-FLUSH WITH LARGE AMOUNTS WATER FOR 15 MIN;INGEST-RINSE MOUTH; GET
MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF
OVEREXPOSURE.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, state
s, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of
this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.