

SHERWIN INC -- DUBL-CHEK MPF -- 6850-01-196-5472

=====
Product Identification
=====

Product ID:DUBL-CHEK MPF
MSDS Date:10/01/1987
FSC:6850
NIIN:01-196-5472
MSDS Number: BJQYT
=== Responsible Party ===
Company Name:SHERWIN INC
Address:5530 BORWICK AVE
City:SOUTH GATE
State:CA
ZIP:90280-7402
Country:US
Info Phone Num:213-861-6324
Emergency Phone Num:213-861-6324
CAGE:21405
=== Contractor Identifica
tion ===
Company Name:SHERWIN INC.
Address:5530 BORWICK AVE.
City:SOUTH GATE
State:CA
ZIP:90280-7402
Country:US
Phone:562-861-6324/FAX 923-8370
CAGE:21405

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE
CAS:64742-46-7
RTECS #:JN9379645
Other REC Limits:NONE ESTABLISHED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:N

TP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE IRRITATION ON CONTACT.

INHALATION MAY CASUE LIGHT HEADINESS.

Effects of Overexposure:MAY BE IRRITATING.

Medical Cond Aggravated by Exposure:NONE STATED.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER; SKIN: WASH AFFECTED AREAS, & REMOVE CONTAMINATED CLOTHING; INHALE: REMOVE TO FRESH AIR; INGEST: DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

=====
=== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F/93C

Lower Limits:0.6

Upper Limits:7

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:DO NOT USE DIRECT STREAM OF WATER, IT SPREADS THE FIRE. PRODUCT MAY FLOAT AND REIGNITE.

Unusual Fire/Explosion Hazard:ON BURNING, THIS PRODUCT MAY RELEASE TOXIC FUMES AND VAPORS. FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL FLAMES, REMOVE ALL IGNITION RESOURCES. DIKE AREA IF IT IS A LARGE SPILL. AND PUMP INTO THE CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE STATED.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT SPLASH OR CREATE MISTS OR VAPORS. STORE AWAY FROM HIGH TEMPERATURES AND OPEN FLAMES. KEEP CONTAINERS CLOSED.

Other Precautions:

EMPTIED CONTAINERS RETAIN VAPOR AND PRODUCT RESIDUES.
DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH-APPROVED RESPIRATOR IF VAPORS OR MISTS
ARE GENERATED.

Ventilation:LOCAL EXHAUST IS RECOMMENDED.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:NONE STATED.

Work Hygienic Practices:NONE STATED.

Supplemental Safety and Health

=====

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:450F/232C

Vapor Pres:1

Vapor Density:> 5

Spec Gravity:0.81

Evaporation Rate & Reference:0.01 (BYTYL ACETATE =1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:FAINT PETROLEUM ODOR, CLEAR LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS.

Stability Condition to Avoid:OPEN FLAMES.

Hazardous Decomposition Produ

cts:CARBON MONOXIDE AND OTHER UNIDENTIFIED

ORGANIC COMPOUNDS MAY BE FOUND UPON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:TO COMPLY WITH LOCAL, STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this informa

tion to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.