View NSN Online: https://aerobasegroup.com/nsn/8030-01-289-4502

ULTRASEAL INTERNATIONAL, INC -- ULTRASEAL TIRE SEALANT 4150 -- 8030-01-289-4502

Product ID:ULTRASEAL TIRE SEALANT 4150 MSDS Date:02/09/1990 FSC:8030 NIIN:01-289-4502 MSDS Number: BJQZK === Responsible Party === Company Name: ULTRASEAL INTERNATIONAL, INC Address:1100 N WILCOX AVE **City:LOS ANGELES** State:CA ZIP:90038 Country:US Info Phone Num:213-466-1226 Emergency Phone Num:213-466-1226 CAGE:0CWF7 === Contractor Identification === Company Name: ULTRASEAL INTERNATIONAL, INC Address:1100 N WILCOX AVE Box:City:LOS ANGELES State:CA ZIP:90038 Country:US Phone:213-466-1226 CAGE:0CWF7

Ingred Name:ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: 28% Other REC Limits:NONE SPECIFIED OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

=====

| ====================================== |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Routes of Entry: Inhalation:UNKNOWN Skin:UNKNOWN Ingestion:YES Health Hazards Acute and Chronic:INGESTION: NAUSEA. Medical Cond Aggravated by Exposure:NONE. |
| ====================================== |
| First Aid:IF SWALLOWED, GIVE 1 TABLESPOON SALT IN GLASS OF WARM WATER TO INDUCE VOMITING, REPEAT UNTIL VOMIT FLUIDS ARE CLEAR. |
| ====================================== |
| Spil I Release Procedures:WILL CURE FROM EXPOSURE TO AIR. WIPE OR SHOVEL INTO NON-HAZARDOUS BIN. |
| ====================================== |
| Handling and Storage Precautions:NONE. Other Precautions:NONE. |
| ========= Exposure Controls/Personal Protection ============== |
| Respiratory Protection:NONE NEEDED. Ventilation:NONE NEEDED. Protective Gloves:NONE NEEDED. Eye Protection:NONE. Other Protective Equipment:NONE. Work Hygienic Practices:WASH HANDS AFTER USE. Supplemen tal Safety and Health |
| ====================================== |
| Boiling Pt:B.P. Text:387F,197C Vapor Pres:20 Vapor Density:1.0 Spec Gravity:108 Evaporation Rate & amp; Reference:1.0 BUTYL ACETATE Solubility in Water:90 Appearance and Odor:BLUE OR RED, GLYCOL ODOR. |
| ====================================== |
| Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:NONE. |
| ====================================== |

Waste Disposal Methods:CURED WASTE CAN BE DISPOSED IN NON-HAZARDOUS LAND FILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to ver ify and

assume responsibility for the suitability of this information to their particular situation.