BOSTIK -- ANTI-SEIZE COMPOUND (MIXTURE) NEV-SZ REG -- 8030-01-293-5630

Product ID:ANTI-SEIZE COMPOUND (MIXTURE) NEV-SZ REG MSDS Date:07/02/1986 FSC:8030 NIIN:01-293-5630 **MSDS Number: BJQZL** === Responsible Party === Company Name:BOSTIK Address: BOSTON STREET City:MIDDLETON State:MA ZIP:01949 Country:US Info Phone Num:617-777-0100 Emergency Phone Num:617-777-0100 Ρ reparer's Name:D. C. MOLBERG CAGE:60775 === Contractor Identification === Company Name: BOSTIK Address:BOSTON ST City:MIDDLETON State:MA ZIP:01949 Country:US Phone:508-777-0100 CAGE:60775 Company Name: R. H. DOBBERPUHL, INC CAGE:2W308

Ingred Name:COPPER (SARA III) CAS:7440-50-8 RTECS #:GL5325000 Fraction by Wt: 14.7% Other REC Limits:NONE SPECIFIED OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9192 EPA Rpt Qty:5000 LB S DOT Rpt Qty:5000 LBS

Ingred Name:ZINC OXIDE CAS:1314-13-2 RTECS #:ZH4810000 Fraction by Wt: 2.3% Other REC Limits:NONE SPECIFIED OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:ALUMINUM (SARA III) CAS:7429-90-5 RTECS #:BD0330000 Fraction by Wt: 2.6% Other REC Limits:NONE SPECIFIED OSHA PEL:15MG/M3 DUST/5 FUME ACGIH TLV:10MG/M3 DUST; 9192

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITATION. Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

Flash Point:NONE Extinguishing Media:WATER SPRAY, FOAM, DRY CHEMICAL, CARBON DIOXIDE. Fire Fi ghting Procedures:USE SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:USE SELF-CONTAINED BREATHING APPARATUS.

Spill Release Procedures: IF LIQUID, SOAK UP WITH ABSORBENT MATERIAL SUCH AS SAND, EARTH, SWEEPING COMPOUND OR SOME OTHER ABSORBENT MATERIAL. PACKAGE ABSORBENT MATERIAL OR SOLID PRODUCT IN STEEL DRUMS WHICH ARE IN GOOD CONDITI ON. THOROUGHLY CLEAN AREA WHERE SPILL OCCURRED.

=======

Handling and Storage Precautions:STORE IN A COOL LOCATION (60-80F) AWAY
FROM SUNLIGHT & ANY SOURCE OF HEAT. KEEP CONTAINER TIGHTLY CLOSED
WHEN NOT BEING USED.
Other Precautions:USE WITH ADEQUATE VENTILATION, AVOID PROLONGED OR
REPEATED BREATHING OF VAPORS. AVOID SKIN CONTACT.

======= Exposure Controls/Personal Protection ==========

Ventilation:NOT NORMALLY REQUIRED. Protective Gloves:IMPERVIOUS PLASTIC. Eye Protec tion:SAFETY GLASSES OR FULL FACE SHIELD. Other Protective Equipment:SAFETY SHOWER AND EYE BATH. Supplemental Safety and Health

Spec Gravity:1.37 Solubility in Water:0.0% Appearance and Odor:SILVERY GRAY ANTI-SEIZE WITH A GREASELIKE ODOR. Percent Volatiles by Volume:0.0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS AND ACIDS. Hazardous Decompos ition Products:MAYBE FROM COMBUSTION OF MAT'L: CARBON DIOXIDE, CARBON MONOXIDE, WATER VAPOR, OXIDES OF NITROGEN, INNOCUOUS/TOXIC FUME.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. BE AWARE THAT STATE AND LOCAL REQUIREMENTS MAY DIFFER WIDELY DEPENDING ON LOCATION AND IN MANY CASES BE DIFFERENT FROM FEDERAL RULES . NOT CLASSIFED AS A HAZARDOUS MATERIAL.

Disclaim

er (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.