

DOW CORNING CORP -- DOW CORNING (R) 7 RELEASE PASTE COMPOUND -- 6150-00-975-0712
===== Product Identification =====

Product ID:DOW CORNING (R) 7 RELEASE PASTE COMPOUND

MSDS Date:01/01/1987

FSC:6150

NIIN:00-975-0712

MSDS Number: BJRGK

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-600

0

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:719

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA GEL
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 8%
Other REC Limits:NONE SPECIFIED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE-MILD IRRITATION.
SKIN/INHALE/DIGEST-NO INJURY IS LIKELY IF EXPO
SURE IS LESS THAN 8
HOURS.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE-TEMPORARY DISCOMFORT WITH MILD REDNESS AND
DRYNESS SIMILIAR TO WINDBURN. SKIN-NO ADVERSE EFFECTS. INHALE-NO
INJURY IS LIKELY. INGEST-SMALL AMOUNTS TRANSFERRED TO THE MOUTH BY
FINGERS DURING USE, E TC., SHOULD NOT INJURE. SWALLOWING LARGE
AMOUNTS MAT CAUSE DIGESTIVE DISCOMFORT.

Medical Cond Aggravated by

Exposure:NO INJURY FROM SILICA SHOULD OCCUR.

IF USE CREATES DUST SOME RESPIRATORY INJURY MAY OCCUR. PRODUCT MAY
ENHANCE ALLERGIC CONDITIONS OF SOME PEOPLE, BUT NO MEDICAL
CONDITIONS SHOULD BE AGGRAVATED.

=====
First Aid Measures
=====

First Aid:EYE-IMMEDIATELY FLUSH WITH WATER. SKIN-WIPE OFF AND FLUSH
WITH WATER. INHALE-NO FIRST AID SHOULD BE NEEDED. ORAL-NO FIRST AID
SHOULD BE NEEDED.

=====
Fire Fighting Measures
=====

=====

Flash Point Method:COC

Flash Point:212F,100C

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND A SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES.

===== Handling and Storage =====

Handling and Storage Precautions:USE REASONABLE CARE AND CAUTION.

Other Precautions:TRACES OF FORMALDEHYDE (CARCINOGEN) MAY FORM IF HEATED ABOVE 300F/149C. PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE WHEN HANDLING AT ELEVATED TEMPERATURES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO RESPIRATOR PROTECTION SHOULD BE NEEDED.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS RECOMMENDED.

Protective Gloves:NON

E NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AT MEALTIME AND AT END OF SHIFT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V7

Vapor Pres: