

THE LINCOLN ELECTRIC CO -- FLEETWELD 5P (AWS E6010) -- 3439-00-262-2669

===== Product Identification =====

Product ID:FLEETWELD 5P (AWS E6010)

MSDS Date:01/15/1990

FSC:3439

NIIN:00-262-2669

MSDS Number: BJRMP

=== Responsible Party ===

Company Name:THE LINCOLN ELECTRIC CO

Address:22801 ST CLAIR AVE

City:CLEVELAND

State:OH

ZIP:44117-1199

Country:US

Info Phone Num:216-481-8100

Emergency Phone Num:21

6-481-8100

CAGE:HO076

=== Contractor Identification ===

Company Name:THE LINCOLN ELECTRIC CO

Address:22801 ST CLAIR AVE

Box:City:EUCLID

State:OH

ZIP:44117-1199

Country:US

Phone:216-481-8100

CAGE:36232

Company Name:THE LINCOLN ELECTRIC COMPANY

CAGE:HO076

===== Composition/Information on Ingredients =====

Ingred Name:CELLULOSE AND OTHER CARBONYDRATES

CAS:65996-61-4

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 RESP.DUST

ACGIH TLV:10 MG/M3 NUISANCE

Ingre

d Name:SODIUM SILICATE
CAS:1344-09-8
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 RESP.DUST
ACGIH TLV:10 MG/M3 NUISANCE

Ingred Name:IRON
CAS:65996-67-0
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 RESP.DUST
ACGIH TLV:10 MG/M3 NUISANCE

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MANGANESE (SARA III)
CAS:7439
-96-5
RTECS #:OO9275000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:MAGNESIUM OXIDE
CAS:1309-48-4
RTECS #:OM3850000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 PARTICULATE
ACGIH TLV:10 MG/M3;TDUST; 9293

Ingred Name:KAOLIN
CAS:1332-58-7
RTECS #:GF1670500
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:IRON OXIDE
CAS:65996-74-9
Fr

action by Wt: < 0.5%
OSHA PEL:10 MG/M3
ACGIH TLV:5 MG/M3

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: < 0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:GRAPHITE, NATURAL
CAS:7782-42-5
RTECS #:MD9659600
Fraction by Wt: < 0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MPPCF RDUST
ACGIH TLV:2 MG/M3 RDUST; 9293

=====
===== Hazards Identification =====

Routes
of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:FUMES AND GASES CAN BE DANGEROUS TO
YOUR HEALTH. ARC RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK
CAN KILL. NOISE CAN DAMAGE HEARING.
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.
Effects of Overexposure:ACUTE:METALLIC
TASTE,NAUSEA,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE AND THROAT.
CHRONIC:EXCESSIVE LEVELS MAY CAUSE SIDER
OSIS (IRON DEPOSITS IN
LUNGS) AND AFFECT PULMONARY FUNCTION.
Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY
OR ALLERGIC CONDITIONS.HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG
SMOKERS.

=====
===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE AND OBTAIN PROMPT MEDICAL ATTENTION. IF
NOT BREATHING,GIVE CPR/OXYGEN. EMPLOY FIRST AID TECHNIQUES
RECOMMENDED BY AMERICAN RED CROSS.

=====
===== Fire Fighti

ng Measures =====

Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:WELDING ARCS, SPARKS, ETC. MAY IGNITE COMBUSTIBLE MATERIAL.

===== Accidental Release Measures =====

Spill Release P

rocedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY AREA. ELECTRODES EXPOSED TO MOISTURE MAY EXPLODE VIOLENTLY IF USED. DRY MOIST RODS BY BAKING AT 300F FOR TEN HOURS.

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES.MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES.AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA. WELDING ARC CAN IGNITE COMBUSTIBLES AND FLAMMABLES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:LOCAL EXHAUST TO KEEP BELOW TLV.

Protective Gloves:WELDER'S GLOVES.

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH,ARM PROTECTOR,APRON,HAT AND SHOULDER PROTECTION. AIR SAMPLING TO DETERMINE CORRECTIVE MEASURES.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKING OR USING SANITARY FACILITIES.

Supplemental Safety and Health NONE.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:WELDING ROD.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:

IRON OXIDE, COMPLEX OXIDES OF
MANGANESE, SILICON AND SODIUM, CARBON MONOXIDE, CARBON DIOXIDE,
OZONE, NITROGEN OXIDES

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT WITH YOUR LOCAL ENVIRONMENTAL
OFFICER.DISPOSE OF FUMES,FLUX OR WELD GRINDING RESIDUE FROM THE
WORK AREA OR FROM FILTERS IN ACCORDANCE WITH FEDERAL,STATE AND
LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.