View NSN Online: https://aerobasegroup.com/nsn/6830-00-935-9895

ALLIED CORP., ALLIED CHEMICAL, CSS DEPT. -- GENETRON 12 DICHLORODIFLUOROMETHANE -- 6830-00-935-9895

Product ID:GENETRON 12 DICHLORODIFLUOROMETHANE MSDS Date:08/01/1985 FSC:6830 NIIN:00-935-9895 **MSDS Number: BJRPX** === Responsible Party === Company Name: ALLIED CORP., ALLIED CHEMICAL, CSS DEPT. Box:1139R City:MORRISTOWN State:NJ ZIP:07960 Country:US Info Phone Num:20 1-455-4157 Emergency Phone Num:201-455-2000 CAGE: JO859 === Contractor Identification === Company Name: ALLIED CORP., ALLIED CHEMICAL, CSS DEPT. Address:COLUMBIA RD & PARK AVE Box:1087R City:MORRISTOWN State:NJ ZIP:07960 Country:US Phone:201-455-2000 CAGE: JO859 Company Name: ALLIED-SIGNAL INC Address:Box:2332R City:MORRISTOWN State:NJ ZIP:07962-2332 Country:US Phone:201-455-4414 CAGE:1L164 **Company Name: SANCHEZ & ASSOCIATES** Address:476 WEST FOGG STREET Box:1649 City:COLTON (MAY BE OUT OF BUSINESS !)

State:CA ZIP:92324 Country:US Phone:714-370-3921/FAX824-0341 ALL WRONG# CAGE:0HF19

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III) CAS:76-13-1 RTECS #:KJ4000000 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED OSHA PEL:1000PPM/1250STEL ACGIH TLV:1000PPM/1250STEL9192 Ozone Depleting Chemical:1

LD50 LC50 Mixture:LD 50 ORAL

RAT 45MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: VAPORS HEAVIER THAN AIR AND CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE FOR BREATHING. BREATHING HIGH CONCENTRATIONS OF VAPOR CAUSE HEAVYNESS IN THE HEAD,DROWSINESS, GIDDINESS,SHORT NESS OF BREATH,AND MAY LEAD TO NARCOSIS,CARDIAC IRREGULARITIES,UNCONSCIOUSNESS OR DEATH. SKIN:MAY DEFAT.EYES:IRRITATION.

Exp

lanation of Carcinogenicity: FREON 12 IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA.

Effects of Overexposure: INHALATION: BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, AND MAY LEAD TO NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. SKIN: IRRITANT. EXCES SIVE CONTACT MAY DEFAT SKIN. EYES: VAPOR- MILD IRRITANT; LIQ - IRRITANT; INGESTION: LOW TOXICITY.

Medical Cond Aggravated by Exposure:SKIN DISEASE - FREON 113 IS A

DEFATTING AGENT AND CAN CAUSE DERMATITIS ON PROLONGED EXPOSURE. PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS AGENT.

First Aid:INHALATION: REMOVE TO FRESH AIR, CALL A PHYSICIAN. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.IF BREATHING IS DIFFICULT, GIVE OXYGEN. DO NOT GIVE EPINEPHRINE OR SIMILAR DRUGS. EYE: FLUSH WITH WATER . SKIN: FLUSH WITH WATER. IF IRRITATIO NPERSISTS, GET

MEDICAL ATTENTION. ORAL: GET MEDICAL ATTENTION IMMEDIATELY. INDUCE VOMITING BY GIVING TWO GLASSES OF WATER. CALL A PHYSICIAN.

Flash Point:NONE

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNO

FF.

Unusual Fire/Explosion Hazard:MATERIAL A LIQ UNDER ITS OWN VAPOR PRESSURE. EXOTHERMIC REACTION OCCURS WITH MOLTEN ALUMINUM,BARIUM,AND LITHIUM SHAVINGS OR POWDER.

Spill Release Procedures: VENTILATE AREA. EVACUATE UNPROTECTED PERSONS. ELIMINATE IGNITION SOURCES SND SHUT OFF LEAK. ABSORB LIQUID WITH COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS.LARGE SPILL: DIKE UP WITHABSORBENT AND PUMP INTO DRUMS, MAKING SURE PUMP DOES NOT GET OVERHEATD Neutralizing Agent:NONE

Handling and Storage Precautions:STORE IN A CLEAN, COOL, DRY AND
WELL-VENTILATED AREA. PROTECT CONTAINERS FROM PHYSICAL DAMAGE AND
KEEP CLOSED. OPEN BUNG SLOWLY AND CAUTIOSLY.
Other Precautions:AVOID BREATHING VAPOR, LIQUID CONTACT WITH EYES, SKIN

OR CLOTHING. TANK-CLEANING VAPOR, LIQUID CONTACT WITH EYES, SKIN OR CLOTHING. TANK-CLEANING PERSONNEL SHOULD USE ONLY FORMAL TANK ENTRY PROCEDURE BASED ON RECOGNIZED SAFE TY PRINCIPLES. EMPTY CONTAINERS MAY CONTA IN PRODUCT RESIDUES/VAPORS. Respiratory Protection: NONE REQUIRED FOR ADEQUATELY VENTED WORK SITUATIONS. FOR ACCIDENTAL OR NON-VENTILATED SITUATIONS, USE A SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR RESPIRATOR, APPROVED BY NIOSH. Ventilation: PROVIDE LOCAL EXHAUST AT FILLING ZONES AND OTHER OPERATING SPACES WHERE LEAKAGE IS PROBABLE. MECHANICAL FOR OTHER. Prot ective Gloves: BUTYL RUBBER, PVA OR NEOPRENE Eye Protection: CHEMICAL SPLASH GOGGLES Other Protective Equipment: USE IMPERVIOUS CLOTHING IF THERE IS REPEATED OR PROLONGED CONTACT WITH LIQUID. Work Hygienic Practices: PRE-EXISTING EYES AND SKIN DISORDER MAY BE AGGRAVATED TO EXPOSURE TO THIS PRODUCT. Supplemental Safety and Health NONE HCC:G3 Boiling Pt:B.P. Text:-22F,-30C Vapor Pres:85PSIA@21C Vapor Density:4.26 Spec Gravi ty:1.325 Solubility in Water:NEGLIGIBLE Appearance and Odor: COLORLESS LIQUIFIED GAS WITH FAINT ETHEREAL ODOR Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, FINELY DIVIDED BARIUM, AND LITHIUM. POWDERED ALUMINUM, MAGNESIUM AND ZINC. Stability Condition to Avoid: HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products: DECOMPOSED BY HIGH TEMPERATURES TO FORM HALOGENS, HALO

## GEN ACIDS, AND CARBONYL HALIDES, INCLUDING PHOSGENE.

## Waste Disposal Methods:COMPLY WITH FEDERAL, STATE AND LOCAL REGULATIONS. REMOVE TO A PERMITTED WASTE DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this i nformation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.