View NSN Online: https://aerobasegroup.com/nsn/9150-00-149-7432

HULS AMERICA INC. -- MIL-H-83282C;#0425600;HYDRAULIC FLUID -- 9150-00-149-7432

Product ID:MIL-H-83282C;#0425600;HYDRAULIC FLUID MSDS Date:02/10/1989 FSC:9150 NIIN:00-149-7432 **MSDS Number: BJSDJ** === Responsible Party === Company Name: HULS AMERICA INC. Address:TURNER PLACE Box:365 City:PISCATAWAY State:NJ ZIP:08854 Country:US Info Phone Num:201-763-7173 Emergency Phone Num:201-763-7173 Preparer's Name: P.A. PARKER (DGSC-SSH) CAGE:0DH22 === Contractor Identification === Company Name: HUL AMERICA INC Address:TURNER PLACE Box:365 City:PISCATAWAY State:NJ ZIP:08854-0365 Country:US Phone:201-763-7173 CAGE:0DHB8 **Company Name: HULS AMERICA INC** Address:TURNER PLACE Box:365 City:PISCATAWAY State:NJ ZIP:08854-0365 Country:US Phone:908-981-5016 CAGE:0DH22

Ingred Name:SYNTHETIC HYDROCARBON

=======

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,RESPIRATORY TRACT,CNS EFFECTS LIKE HEADACHE,NAUSEA,VOMITING. CHRONIC:IRRITATION,DERMATITIS POSSIBLE. Explanation of Carcinogenicity:NO DATA PER MSDS Effects of Overexposure:SEE HEALTH HAZARDS DATA. Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

First Aid:SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINUTES,CALL A PHYSICIAN IF NEEDED.INHALATION:REMOVE TO FRESH AIR,CALL A PHYSICIAN. INGESTION:DO NOT INDUCE VOMITING;CALL A PH YSICIAN IMMEDIATELY.

Flash Point Method:COC Flash Point:410F/210C Lower Limits:1.0 Upper Limits:6.0 Extinguishing Media:WATER FOG,DRY CHEMICAL,FOAM,CO\*2. Fire Fighting Procedures:USE NIOSH/MSH A APPROVED SCBA IN AN ENCLOSED AREA. Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS;COOL WITH WATER SPRAY.

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; REMO ALL IGNITION SOURCES; CONTAIN FREE LIQUID; USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

Handling and Storage Pre

## cautions:STORE IN COOL,DRY AND WELL VENTILATED AREA;KEEP AWAY FROM HEAT,OPEN FLAMES.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF PEL/TLV. Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV. Protective Gloves:IMPERVIOUS. Eye Protection:CHEMICAL GOGGLES/FACE SHIELD. Other Protective Equipment:APRON,SAFETY SHOWER;EYE-WASH FACILITIES. Work Hygienic Practices:AVOID CONTACT WITH EYES & SKI N;DO NOT BREATHE VAPORS/MIST;WASH THOROUGHLY AFTER EACH USE;DO NOT USE CONTAMINATED CLOTH Supplemental Safety and Health MSDS COPIED FROM SAME MFR DIFFERENT SIZE

Boiling Pt:B.P. Text:520F/271C Vapor Pres:0.02 MMHG Vapor Density:>1.0 Spec Gravity: