

PERMAGILE INDUSTRIES, INC -- IC-4200-56840-B, CERAMICAST 4-200 -- 8030-00-229-8735
===== Product Identification =====

Product ID:IC-4200-56840-B, CERAMICAST 4-200

MSDS Date:10/04/1989

FSC:8030

NIIN:00-229-8735

MSDS Number: BJVFY

=== Responsible Party ===

Company Name:PERMAGILE INDUSTRIES, INC

Address:101 COMMERCIAL STREET

City:PLAINVIEW

State:NY

ZIP:11803

Info Phone Num:(800) 645-7546

Emergency P

Home Num:(516) 349-1100

Preparer's Name:LAWRENCE J. DE MAIO

CAGE:13549

=== Contractor Identification ===

Company Name:PERMAGILE INDUSTRIES INC

Address:101 COMMERCIAL STREET

City:PLAINVIEW

State:NY

ZIP:11803

Country:US

Phone:516-349-1100/800-424-9300(CHEMTREC)

CAGE:13549

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC AMIDO AMINE

Fraction by Wt: 86.67%

===== Hazards Identification =====

Routes of Entry: Inhalation:YE

S Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: RESPIRATORY TRACT

IRRITATION, HEADACHE, DIZZINESS, NAUSEA & VOMITING. SKIN:

SENSITIZATION, OTHER ALLERGIC RESPONSES, & IRRITATION. EYES:

IRRITATING, BLINDNESS & PERMANENT INJURY.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATING, BLINDNESS & PERMANENT INJURY.

SKIN: SENSITIZATION, OTHER ALLERGIC RESPONSES, & IRRITATION.

INHALATI

ON: HEADACHE, DIZZINESS, NAUSEA & VOMITING.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: WASH W/SOAP & WATER.
EYES: FLUSH W/WATER FOR 15 MINUTES, OBTAIN MEDICAL ATTENTION IN ALL
CASES.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC

Flash Point:300F

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:USE WATER FOG COOL CONTAINERS. CLOSE ALL
VALVES

& SHUT OFF ALL POWER TO THE AREA. USE SELF-CONTAINED
BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID. OVERHEATING MAY CAUSE
CONTAINER TO RUPTURE.

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB W/SAND & DISPOSE OF IN APPROVED MANNER.
DIKE AREA W/SAND TO CONTAIN SPILLED LIQUID. PREVENT SPILLAGE FROM
ENTERING UNDERGROUND WATER SYSTEMS.

=====
Handling and Storage
=====

H

Handling and Storage Precautions:OVERHEATING MAY CAUSE CONTAINER TO
RUPTURE. STORE IN A COOL, DRY PLACE. KEEP AWAY FROM OPEN FLAMES.
CHECK ALL CONTAINERS FOR LEAKS.

Other Precautions:AVOID BREATHING & CONTACT W/SKIN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT ORDINARILY REQUIRED

Ventilation:PROVIDE ADEQUATE CROSS AIR CIRCULATION

Protective Gloves:IMPERVIOUS TO SOLVENTS

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:EYEWASH ST

ATION, BATH SHOWER, BARRIER CREAM

Supplemental Safety and Health

KEY1:T6. THIS ENTRY DESCRIBES PART B OF A TWO PART KIT. SEE THIS SAME
NSN, P/N IND A AND P/N IND C, FOR PART A DATA.

===== Physical/Chemical Properties =====

HCC:T6

Spec Gravity:1.06

Evaporation Rate & Reference:SLOWER THAN N-BU AC

Solubility in Water: