View NSN Online: https://aerobasegroup.com/nsn/2640-00-922-6921

PEMCO ADHESIVES, INC -- M100 PEMCO ADHESIVE 1599 -- 2640-00-922-6921

========= Product Identification ==============

Product ID:M100 PEMCO ADHESIVE 1599

MSDS Date:01/01/1987

FSC:2640

NIIN:00-922-6921

MSDS Number: BJWBM === Responsible Party ===

Company Name: PEMCO ADHESIVES, INC

Box:247

City: AUBURN

State:IN ZIP:46706

Info Phone Num:(219) 925-3368

Emergency Phone Num: (219) 925-3368

CAGE:OPES8

=== Contractor Ide

ntification ===

Company Name: ADAMS PSP INC

Address:355 UNIONVILLE RD

Box:City:BUTLER

State:PA ZIP:16003 Country:US CAGE:17705

Company Name: PEMCO ADHESIVES, INC

Box:247

City: AUBURN

State:IN ZIP:46706

Phone: (219) 925-3368

CAGE:OPES8

======= Composition/Information on Ingredients ========

Ingred Name:RUBBER ACGIH TLV:350 PPM

Ingred Name: RESIN

Other REC Limits:10 MG/CUM (DUST)

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1 ========== Hazards Identification ===================== Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: MILD IRRITATION. SKIN: DEFATTING & MILD IRRITATION. INHALATION: ANESTHETIC EFFECT 500 TO 10 PPM. **Explanation of Ca** rcinogenicity:NONE Effects of Overexposure: EYE: MILD IRRITATION. SKIN: DEFATTING & MILD IRRITATION, INHALATION: ANESTHETIC EFFECT. First Aid:SKIN/EYES: FLUSH W/WATR FOR 15 MINUTES. INHALATION: REMOVE TO FRESH AIR. KEEP WARM & QUIET. IF BREATHING IS STOPPED, GIVE ARTIFICIAL RESPIRATION. OBTAIN MEDICAL ATTENTION IN ALL CASES. Extinguishing Media: **SELF-EXTINGUISHING** Fire Fighting Procedures: SELF CONTAINED RESPIRATORY EQUIPMENT. ========== Accidental Release Measures ================ Spill Release Procedures: MOP UP, TREAT W/ABSORBANT, AREA BURY ABSORBED MATERIAL. KEEP AWAY FROM WATER SUPPLY & INHABITED BLDGS. ============= Handling and Storage ========================== Handling and Storage Precautions: AVOID BREATHING VAPORS. ====== Exposure Controls/Personal Protection ======== Ventilation:LOCAL E

Wt: 85%

Other REC Limits:350 PPM (CL) OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

