

AMERICAN LUBRICATING CO -- FOG OIL -- 9150-00-261-7895

=====  
Product Identification  
=====

Product ID:FOG OIL  
MSDS Date:08/18/1995  
FSC:9150  
NIIN:00-261-7895  
MSDS Number: BJJJZ  
=== Responsible Party ===  
Company Name:AMERICAN LUBRICATING CO  
Address:500 SOUTH FRONT STREET  
Box:258  
City:MEMPHIS  
State:TN  
ZIP:38101  
Country:US  
Info Phone Num:800-786-2526/901-527-4707  
Emergency Phone Num:800-786-2526/901-527-4707  
Preparer's Name:CHIP ARMSTRONG  
CAGE:0MLS2  
=== Contractor Identification ===  
Company Name:AMERICAN LUBRICATING CO  
Address:500 SOUTH FRONT STREET  
Box:258  
City:MEMPHIS  
State:TN  
ZIP:38101  
Country:US  
Phone:901-527-4707  
CAGE:0MLS2

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL OIL (LUBRICATING OIL)  
CAS:64742-53-6  
RTECS #:PY8036000  
Fraction by Wt: 100%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

=====

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:LETHAL DOSE 150LB HUMAN:1PT TO 1QT.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED/REPEATED LIQUID CONTACT W/SKIN WILL DRY & DEFAT SKIN, LEADING TO IRRIT & DERM. INHAL OF FUMES IN HIGH CONCEN MAY RESULT IN DIZZ, HEADACHE, RESP IRRIT, OR UNCONSC.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN T HIS PRODUCT IS

LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:SKIN WILL DRY & DEFAT. SKIN IRRIT, DERMITITIS.

DIZZINESS, HEADACHE, RESPIRATORY IRRITATION, UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
First Aid Measures  
=====

First Aid:IF OVERCOME BY FUMES REMOVE FROM EXPO IMMED.CALL PHYSICIAN.BREATH IRREG/STOP START RESUSCITATION/ADMINISTER OXYG. INGEST DO NOT INDUCE VOMIT.

CALL PHYSICIAN. SKIN CONTACT REMOVE ANY

CONTAMIN CLOTH.WASH SKIN W/SOAP/WARM WATER.IRRIT PERSISTS CALL PHYSICIAN. SPLASHED INTO EYES FLUSH W/CLEAR WATER FOR 15MINS.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC

Flash Point:320F,160C

Autoignition Temp:Autoignition Temp Text:675F

Lower Limits:N/D

Upper Limits:N/D

Extinguishing Media:CO2, WATER SPRAY, OR FOG, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:COOL EXPOSED CONTAINERS W/WATER SPRAY. AVOID

BREATHING FUMES.

Unusual Fire/Explosion Hazard:PRESSURE INCREASED IN OVER HEATED, CLOSED CONTAINERS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE IGN SOURCES.KEEP PEOPLE AWAY.RECOVER LIQUID.ADD ABSORBENT(SAND/SAWDUST/ETC)TO SPILL AREA.MINIMIZE BREATHING OF FUMES.VENTILATE CONFINED SPACES.OPEN ALL WINDOWS/DOORS.ADVISE AUTHORITIES IF PRODU CT ENTER SEWERS/ETC.

Neutralizing Agent:NOT REQUIED.

=====

Handling and Storage =====

Handling and Storage Precautions:KEEP CNTNRS CLSD WHEN NOT IN USE.DO NOT HANDLE/STORE NEAR HEAT/FLAMES.

Other Precautions:AVOID BREATH FUMES.WASH SKIN THOROUGHLY W/SOAP/WATER AFTER HANDLING.USE CHEMICAL RESISTANT GLOVES/APRON.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED, RESPIRATOR FOR MIST.

Ventilation:LOCAL:SAPCE VELOCITY GREATER THAN 60CFM. MECHANICAL:NO SPECIAL EQ

UIPMENT.

Protective Gloves:IMPERVIOUS,CHEM RESISTANT GLOVES.

Eye Protection:GOGGLES/FACE SHIELD.

Other Protective Equipment:CHEMICAL RESISTANT APRON.

Work Hygienic Practices:IF CLOTHES BECOME CONTAMIN CHANGE TO CLEAN CLOTH.DO NOT WEAR CONTAMIN CLOTHES TIL THOROUGHLY LAUNDERED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:620F,327C

Decomp Temp:Decomp Text:300F,149C

Vapor Pres: