View NSN Online: https://aerobasegroup.com/nsn/7930-00-269-1272

OIL-DRI CORPORATION OF AMERICA -- OIL-DRI FLOOR ABSORBENT -- 7930-00-269-1272

Product ID:OIL-DRI FLOOR ABSORBENT

MSDS Date:06/06/1990

FSC:7930

NIIN:00-269-1272

MSDS Number: BJXLB === Responsible Party ===

Company Name: OIL-DRI CORPORATION OF AMERICA

Address:520 N. MICHIGAN AVE.

City:CHICAGO

State:IL ZIP:60611 Country:US

Info Phone Num:312-321-1515

Emergency Phone Num:800-621-7191

Preparer's Name: W. F. MOLL

CAGE:LO041

=== Contractor Identification ===

Company Name: OIL-DRI CORP OF AMERICA

Address:520 N MICHIGAN AVE

Box:City:CHICAGO

State:IL

ZIP:60611-3702

Country:US CAGE:85983

Company Name: OIL-DRI CORPORATION OF AMERICA

CAGE:LO041

======= Composition/Information on Ingredients ========

Ingred Name: NON-HAZARDOUS INGREDIENTS

Other REC Limits: NONE SPECIFIED

Ingred Name:THIS MAT'L CONTAINS CRYSTALLINE SILICA AS QUARTZ(CAS 14808-60-7).HOWEV

ER CRYSTALLINE SILICA IN THE RESP RANGE IS BELOW* RTECS #:9999999ZZ Other REC Limits: NONE SPECIFIED Ingred Name: *THE OSHA CONCEN LIMIT OF 0.1%.IN ADDITION, APPL DATA INDICATE THAT RESP QUARTZ IS WELL BELOW PEL AND TLV, BOTH 0.1MG/M. RTECS #:9999999ZZ Other REC Limits: NONE SPECIFIED ============== Hazards Identification ======================= Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:REPEATED INHALATION OF EXCESSIVE **CONCENTRATIONS OF** ANY DUST INCLUDING THIS MATERIAL MAY LEAD TO LUNG INJURY. Explanation of Carcinogenicity: IARC HAS PLACE RESP CRYSTALINE SILICA IN GROUP 2A.CRYSTALLINE SILICA, INCLUDE QUARTZ IS PRESENT IN MANY MINERAL PRODUCTS. Effects of Overexposure: REPEATED INHALATION OF EXCESSIVE CONCENTRATIONS OF DUST MAY CAUSE SHORTNESS OF BREATH. ======== Accidental Release Measures ============ Spill Release Procedures: VACUUM OR SCOOP UP ====== Exposure Controls/Personal Protec tion ======= Respiratory Protection: DUST RESPIRATOR IN COMPLIANCE WITH NIOSH, IF EXCESSIVE DUST IS GENERATED. Ventilation:LOCAL EXHAUST Work Hygienic Practices: NORMAL GOOD WORK PRACTICE. Supplemental Safety and Health ========= Physical/Chemical Properties =========== Spec Gravity:2.2 Solubility in Water: INSOLUBLE Appearance and Odor: GRET TO TAN, ODORLESS GRANAULES ======== Stability and Reactivity Data ========== Stability Indicator/Materials

to Avoid:YES
CONTACT WITH TURPENTINE, VEGETABLE OIL, AND OTHER SATURATED ORGANIC
COMPOUNDS AND WITH HYDROFLUORIC ACID MAY GENERATE HEAT

====== Disposal Considerations ===========

Waste Disposal Methods:UNUSED MATERIAL MAY BE DISPOSED OF IN SANITARY LANDFILL. CHECK WITH APPROPRIATE REGULATORY AUTHORITY FOR USED MATERIAL CONTAINING HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.