

CAAP CO INC -- FLUOROELASTOMER, COATING, TY 4, GRAY-36270 -- 8030-01-127-1960

=====
Product Identification
=====

Product ID:FLUOROELASTOMER, COATING, TY 4, GRAY-36270

MSDS Date:03/16/1989

FSC:8030

NIIN:01-127-1960

Kit Part:Y

MSDS Number: BJXSC

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-468-0055

Em

ergency Phone Num:203-877-0375

Preparer's Name:RONALD D. ARENA

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qt

y:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:DIETHYLENE GLYCOL DIMETHYL ETHER (DIGLYME)
CAS:111-96-6
RTECS #:KN3339000
Other REC Limits:NONE SPECIFIED

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:
150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPRIETARY FLUOROELASTOMER COMPOUND
Other REC Limits:NONE SPECIFIED

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Other REC Limits:NONE SPECIFIED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA, CRYSTALLINE - FUSED
CAS:60676-86-0
RTECS #:VV7328

000
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:CHROMIUM OXIDE
CAS:1308-38-9
RTECS #:GB6475000
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG/M3

Ingred Name:CADMIUM SULFOSELENIDE (RED)
CAS:58339-34-7
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.2 MG CD/M3
ACGIH TLV:0.05 MG/M3

Ingred Name:CADMIUM SULFIDE ZINC SULFIDE (YELLOW)
CAS:12442-27-2
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.2 MG CD/M3
ACGIH TLV:0.05 MG/M3

Ingred
Name:COBALT CHROMITE BLUE GREEN SPINEL
CAS:68187-11-1
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1 MG CO/M3
ACGIH TLV:0.1 MG/M3

Ingred Name:COBALT ALUMINATE BLUE SPINEL
CAS:1345-16-0
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.1 MG/M3

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRITATION OF NOSE, THROAT AND
EYES. MAY CAUSE DIZZINESS, NAUSEA, VOMITIN

G OR NARCOSIS. CHRONIC:

IRRITATING TO SKIN, MAY CAUSE DERMATITIS. MAY CAUSE REVERSIBLE TESTICULAR AND SPERM DAMAGE. MAY CAUSE TERATOGENICITY.

Explanation of Carcinogenicity:CADMIUM COMPOUNDS LISTED (NTP)/ SUSPECT (IARC).

Effects of Overexposure:VAPOR EXPOSURE: BURNING EYES, HEADACHE, DIZZINESS, THROAT IRRITATION, LOSS OF APPETITE, AND NAUSEA.

CONTACT: MAY CAUSE IRRITATION OF SKIN, BURNING OF SKIN OR EYES.

Medical Cond Aggravated by Exposure:PRE-EXISTING ALLERGIES, ASTHMA AND

EYE AND SKIN DISORDERS MAY BE AGGRAVATED.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH MUCH WATER AND CALL DOCTOR. SKIN: WASH WITH SOAP & WATER, REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY AND CALL DOCTOR. INGESTION: DO NOT INDUCE VOMITING-CALL A DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:35.0F,1.

7C

Lower Limits:1.4

Upper Limits:10.0

Extinguishing Media:CO2, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:METHOD:FLAMMABLE LIQUIDS. NOT MISCIBLE

W/WATER; WATER USED TO COOL EXPOSED CNTNRS. WEAR FULL EMERGENCY EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE, FLAMMABLE LIQUIDS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:KEEP IGNITION SOURCES AWAY. CONTAIN WITH ABSORBENT MATERIAL. USE PROTECTIVE EQUIPMENT. CLEAN UP ABSORBENT

AND CONTAIN SECURELY. SWEEP AND WET MOP WITH SOAP AND WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP IGNITION SOURCES AWAY. KEEP CLOSED WHEN NOT IN USE. KEEP AREA CLEAN.

Other Precautions:AVOID CONTACT WITH SKIN, EYES AND CLOTHING. IF SPRAYING, DO NOT BREATHE MIST.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED ORGAN

IC VAPOR CANISTER MASK

OR SELF-CONTAINED BREATHING APPARATUS FOR EMERGENCIES.

Ventilation:LOCAL EXHAUST PREFERRED. KEEP CONCENTRATIONS BELOW TLV LEVEL. USE MECHANICAL VENTILATION ALSO.

Protective Gloves:NEOPRENE OR POLYETHYLENE.

Eye Protection:SOLVENT RESISTANT SAFETY GOGGLES.

Other Protective Equipment:RUBBER OR POLYETHYLENE APRON. RUBBER BOOTS FOR SPILLS. SPRAY BOOTH IS RECOMMENDED FOR SPRAY APPLICATIONS.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING. CONTACT

LENSES NOT RECOMMENDED FOR SOLVENTS SINCE EYE INJURY MAY RESULT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175 TO 324F

Vapor Pres:26.1

Vapor Density:3.5

Spec Gravity:0.950

Evaporation Rate & Reference:2.09 (BUTYL ACETATE=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:COLORED VISCOUS LIQUID, KETONE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials

to Avoid:YES

STRONG OXIDIZING AGENTS, CAUSTICS, AMINES, ALDEHYDES, AMMONIA, INORGANIC ACIDS, HALOGENS.

Stability Condition to Avoid:IGNITION SOURCES, HOT SURFACES AND TEMPERATURES ABOVE 100F.

Hazardous Decomposition Products:UNDER FIRE CONDITIONS, OXIDES OF CARBON, HYDROGEN FLUORIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION PREFERRED. RCRA HAZARDOUS IGNITABLE WASTE. DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL

REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.